

No image
available for this
configuration.

MLFB-Ordering data 6FC5303-1AF60-8AA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data		Ambient conditions	
Input voltage	DC 24 V	Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).	
Power consumption, max.	25.0 W		
Mechanical data		Ambient temperature	
Net weight	3.700 kg (8.16 lb)	Operation on the front	0 ... 45 °C (32 ... 113 °F)
Width	464.0 mm (18.27 in)	Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Height	225.0 mm (8.86 in)	Transport	-40 ... 70 °C (-40 ... 158 °F)
Depth	54.0 mm (2.13 in)	Storage	-25 ... 55 °C (-13 ... 131 °F)
Installation depth	140.0 mm (5.51 in)	Relative humidity	
Mounting surface		Operation	5 ... 95 %
		Storage	5 ... 95 %
Cutout width	448.0 mm (17.64 in)	Transport	5 ... 95 %
Cutout height	209.0 mm (8.23 in)	Approvals	
Degree of protection		Certificate of suitability	CE
Rear side	IP00		
Front side	IP54		