

MLFB-Ordering data

6FC5370-2BM03-0AA0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input voltage DC 24 V +20 % -15 %

Power consumption, max. 50 W

General tech. specifications

Mains buffering time 3 ms, 20 ms mit SITOP smart power supply

Mechanical data

Mounting position Vertical

Operator panel Perpendicular

Net weight 2.90 kg (6.39 lb)

Width 265.0 mm (10.43 in)

Height 330.0 mm (12.99 in)

Depth 104.0 mm (4.09 in)

Ambient conditions

Ambient temperature

Operation on the front 0 ... 45 °C (32 ... 113 °F)

Operation at the rear 0 ... 50 °C (32 ... 122 °F)

Storage -20 ... 60 °C (-4 ... 140 °F)

Transport -20 ... 60 °C (-4 ... 140 °F)

Relative humidity

Operation 5 ... 90 %

Storage 5 ... 95 %

Transport 5 ... 95 %

Degree of protection

Front side IP65 With the front flap closed

Rear side IP20 / UL open type

Panel cutout

Width 244.1 mm (9.61 in)

Height 307.1 mm (12.09 in)

Approvals

Certificate of suitability CE, EAC, KC