

MOTION CONNECT 800PLUS

MLFB-Ordering data

6FX8002-5CS11-1DA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Electrical data

|                                          |              |
|------------------------------------------|--------------|
| No. of cores x cross-section mm²         | 4x2.5 C      |
| Test voltage, rms Power conductors       | 4.0 kV       |
| Test voltage, rms Signal conductors      | 2.0 kV       |
| Type with braking lead                   | No           |
| Rated voltage V0/V according to EN 50395 | 600 V/1000 V |

Mechanical data

|                                         |                                       |
|-----------------------------------------|---------------------------------------|
| Type of connection cable engine side    | Conector full thread                  |
| Connector size                          | 1 / M23                               |
| Type of bolting                         | not relevant                          |
| Type of connection cable converter side | Connector SINAMICS S120 Booksize MoMo |
| Maximum cable outer diameter            | 11.0 mm                               |
| Length                                  | 30.0 m                                |
| Weight (without connector)              | 6.00 kg                               |

Static deployment

|                                              |                         |
|----------------------------------------------|-------------------------|
| Smallest bending radius (fixed installation) | 44.0 mm                 |
| Tensile stress, max. Fixed installation      | 50 N/mm² (7252 lbf/in²) |
| Torsional stress                             | Absolute 30°/m          |

Dynamic deployment

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| Smallest bending radius(flexible installation in a cable carriers) | 90.0 mm                 |
| Acceleration horizontal, max                                       | 50 m/s²                 |
| Maximum traversing velocity                                        | 300 m/min               |
| Travel path                                                        | 50 m                    |
| Number of bends, max.                                              | 10,000,000              |
| Tensile load for moving cable, max.                                | 20 N/mm² (2901 lbf/in²) |

MLFB-Ordering data

6FX8002-5CS11-1DA0



Figure similar

Technical data

Ambient temperature

|                                                         |                                                                                 |
|---------------------------------------------------------|---------------------------------------------------------------------------------|
| Operation with permanently installed cable              | -50 ... 80 °C                                                                   |
|                                                         | Module-end power connector 0 ... 55°C, Motor-end power connector -20 ... 80°C   |
| Operation with moving cable                             | -20 ... 60 °C                                                                   |
|                                                         | Module-end power connector 0 ... 55°C                                           |
| Storage                                                 | -20 ... 80 °C                                                                   |
|                                                         | Module-end power connector -20 ... 70°C, Motor-end power connector -20 ... 80°C |
| Kind of connection cable                                | Basis cable                                                                     |
| Material of the cable sheath                            | PUR DESINA color orange RAL 2003                                                |
| Type of insulation                                      | CFC/halogen/silicone-free                                                       |
| Standard for behavior in fire: flame resistance         | EN 60332-1-1 to 1-3                                                             |
| Oil resistance                                          | EN 60811-2-1                                                                    |
| Verification of suitability as authorisation for USA    | UL 758                                                                          |
| Verification of suitability as authorisation for Canada | CSA-C22.2-N.210.2-M90                                                           |