

Product-type designation

Hand-held reading system HawkEye 40



HE40 CODE READER W. BLUETOOTH & USB-CABLE, SIMATIC HAWKEYE 40 HANDH. CODE READ., 1D-BARCODE A. DATA MATRIX, WIRELESS BLUETOOTH RADIO EMITTER; HANDLE INCLUDED, 6' (1.8M) USB- CABLE, AND 1950 MAH LI-ION-AKKU ONLY FOR USE WITH CODES W. MEDIUM UP TO HIGH CONTRAST.

Suitability for installation

1D codes: Int. 2/5, Code 128, Code 93, Code 39, EAN/UPC/JAN, Pharmacode, Postal, Codabar, RSS, Composite, Codablock F, Code 11, Matrix 2of5, MSI Plessey, NEC 2 of 5, Telepen, 2D codes: DMC, PDF417, QR, Micro PDF417, Micro QR, Maxicode, Aztec, GoCode

Optical data

Design of image sensor / of camera	CMOS 1280 x 1024, max. image resolution 1024 x 640
Range	50 ... 375 mm
Range / note	Code-dependent, near/far image field selection
Mounting type / of lens	Integrated
Nature of fluorescent material	Integrated, collimator ray: Visible LED laser light 630 nm, sunlight up to 96890 Lux
Image acquisition frequency / maximum	1 Hz
Type of focusing	Fixed focus

Supply voltage, current consumption, power loss

Type of current supply	Battery operation or USB
Type of battery	Lithium ion accumulator
Battery capacity	1.95 A·h
Operating period / with standard battery / typical	8 h

Permitted ambient conditions

Ambient temperature	
• during operating	0 ... 40 °C

• during storage	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Height of fall / maximum	2 m
Design, dimensions and weight	
Width	97 mm
Height	116 mm
Depth	49 mm
Net weight	0.22 kg
Accessories	Elastomer jacket, metal stands, ergonomic handle with 3.9 Ah battery, Bluetooth modem, ext. charging station incl. power supply unit
letzte Änderung:	Jul 3, 2014