SIEMENS

Product data sheet 6GF3020-1HE45-0XX0

Product-type designation



HawkEye 45 hand-held reading system

HE45 CODE READER AND USB-CABLE SIMATIC
HAWKEYE 45 HANDHELD CODE READER,
1D-BARCODE- AND DATA MATRIX-READER,
LCD-DISPLAY FOR DATA, HANDLE INCLUDED,
AND 6' (1.8M)USB-CABLE ONLY FOR USE WITH CODES
WITH MEDIUM UP TO HIGH CONTRAST

Suitability for installation

1D codes: Int. 2/5, Code 128, Code 93, Code 39, EAN/UPC/JAN, Pharmacode, Postal, Codabar, RSS, Composite, Codablock F, Code 11, Matrix 2of5, MSI Plessy, NEC 2 of 5, Telepen, 2D codes: DMC, PDF417, QR, Micro PDF417, Micro QR, Maxicode, Aztec, GoCode

Optical data		
Design of image sensor / of camera	CMOS 1280 x 1024, max. image resolution 1024 x 640	
Range	50 375 mm	
Range / note	Code-dependent, near/far image field selection	
Mounting type / of lens	Integrated	
Nature of fluorescent material	Integrated, collimator ray: Visible LED laser light 630 nm, sunlight up to 96890 Lux	
Image acquisition frequency / maximum	1 Hz	
Type of focusing	Fixed focus	
Supply voltage, current consumption, power loss		
Type of current supply	via USB	
Type of battery		
Permitted ambient conditions		
Ambient temperature		
during operating	0 40 °C	
during storage	-20 +60 °C	

Relative humidity / at 25 $^{\circ}\text{C}$ / without condensation / during operating / maximum	95 %
Height of fall / maximum	1.2 m
Design, dimensions and weight	
Width	97 mm
Height	116 mm
Depth	49 mm
Net weight	0.24 kg
Accessories	Elastomer jacket, metal stands
letzte Änderung:	Jul 3, 2014