# **SIEMENS**

#### **Product data sheet** 6GF3020-1HE45-2BT0

### Product-type designation



### HawkEye 45 hand-held reading system

HE45 CODE READER W.BLUETOOTH & USB-CABLE, SIMATIC HAWKEYE 45 HANDH. CODE READ.,1D-BARCODE A. DATA MATRIX-CODE READER, LCD-DISPLAY FOR DATA, WIRELESS BLUETOOTH RADIO EMITT., HANDLE INCLUD., 6'(1.8M)USB-CAB AND 1950 MAH LI-ON ACCU, ONLY FOR USE WITH CODES WITH MEDIUM UP TO HIGH CONTRAST.

Suitability for installation

1D codes: Int. 2/5, Code 128, Code 93, Code 39, EAN/UPC/JAN,

Op	otica	l data
_		

Design of image sensor / of camera

Range

Range / note

Mounting type / of lens

Nature of fluorescent material

Image acquisition frequency / maximum

Type of focusing

Pharmacode, Postal, Codabar, RSS, Composite, Codablock F, Code
11, Matrix 2of5, MSI Plessy, NEC 2 of 5, Telepen, 2D codes: DMC,
PDF417, QR, Micro PDF417, Micro QR, Maxicode, Aztec, GoCode

CMOS 1280 x 1024, max. image resolution 1024 x 640

50 ... 375 mm

Code-dependent, near/far image field selection

Integrated

Integrated, collimator ray: Visible LED laser light 630 nm, sunlight up

to 96890 Lux

1 Hz

Fixed focus

## Supply voltage, current consumption, power loss

Type of current supply

Type of battery

Battery capacity

Operating period / with standard battery / typical

Battery operation or USB

Lithium ion accumulator

1.95 A·h

8 h

# Permitted ambient conditions

Ambient temperature

· during operating

0 ... 40 °C

during storage	-20 +60 °C	
Relative humidity / at 25 $^{\circ}\text{C}$ / without condensation / during operating / maximum	95 %	
Height of fall / maximum	1.2 m	
Design, dimensions and weight		
Width	97 mm	
Height	116 mm	
Depth	49 mm	
Net weight	0.26 kg	
Accessories	Elastomer jacket, metal stands, ergonomic handle with 3.9 Ah battery, Bluetooth modem, ext. charging station incl. power supply unit	
letzte Änderung:	Jul 3, 2014	