

Product type designation
Product description

Cable RS232, Sub-D / MV320 connector / low voltage connector
Coiled communication line
RS232-CABLE W/O PS, FOR USE WITH MV320 8' (2.4M), COILED,
NOTE: POWER SUPPLY UNDER 6GF3020-0AC40-0AP2



Suitability for use	Plug-in cable for connecting an MV320 to a PC
Wire length	2.4 m

Electrical data	
Number of electrical connections	3
Type of electrical connection	Sub-D (female, 9 pin, straight) / MV320 connector / low voltage connector (male, 2 pin, 5.5 mm)

Mechanical data	
Net weight	0.17 kg

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx Download Manager 	<p>https://support.industry.siemens.com/cs/ww/en/view/67384972</p> <p>http://www.siemens.com/ident/rfid</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p>

- to website: Industry Online Support

<https://support.industry.siemens.com>

last modified:

10/14/2016