

Data sheet

6GF3420-0AC00-1LT0

Product type designation
Product description

MV420 integration ring light red
Built-in ring light red (618 nm)
SIMATIC MV420 BUILT-IN RINGLIGHT RED MOUNTING
MATERIAL INCLUDED



Suitability for use	For ranges of illumination up to 0.3 m and a flash duration from 120 us to 14 ms
Mechanical data	
Material	Epoxy resin/plastic
Color	green
Permitted ambient conditions	
Ambient temperature	
• during operation	0 ... 50 °C
• during storage	-30 ... +70 °C
• during transport	-30 ... +70 °C
Design, dimensions and weight	
Height	12 mm
Diameter	34 mm
Net weight	5 g
Further Information / Internet Links	
Internet-Link	

- to website: TIA Selection Tool
- to website: Selector SIMATIC NET
SELECTION TOOL
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

last modified:

<http://www.siemens.com/tia-selection-tool>
<https://support.industry.siemens.com/WW/view/en/67384964>
<http://www.siemens.com/iwlan>
<http://www.siemens.com/codereader>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

10/14/2016