

product type designation



MV500 built-in ring light IR basic

MV500 built-in ring I. IR basic For MV500 devices (MLFB: 6GF3540-0CD10, -0GE10, 6GF3550-0CD10, -0GE10; 6GF3560-0HE10, -0LE10)
Lighting: LED 850 Nm, Lighting distance up to 0.8 m; Assembly material enclosed; Use with protective lens barrel (MLFB: 6GF3540-8AC11)

suitability for use

lighting switchable in segments

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

0 ... 50 °C
-30 ... +70 °C
-30 ... +70 °C

further information / internet-Links

Internet-Link

- to website: TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>
<http://www.siemens.com/codereader>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<https://sie.ag/2QdlxcP>

<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

5/20/2021 