

Product type designation

OSM ITP62
SIMATIC NET, OSM ITP62 OPTICAL SWITCH MODULE W. 2 FOC PORTS 100 MBIT/S, 6 ITP-PORTS 10/100 MBIT/S AND 8 DIGITAL INPUTS; REDUNDANT 24V DC SUPPLY, SIGNAL CONTACT, INTEGRATED REDUNDANCY MANAGER WITH NETWORK MANAGEMENT AMBIENT TEMPERATURE MAX. +55 DEGR. C.



Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces	
Number of electrical/optical connections for network components or terminal equipment / maximum	8
Number of electrical connections for network components or terminal equipment	6
Type of electrical connection for network components or terminal equipment	9-pin Sub-D socket (10/100 Mbit/s)
Number of optical interfaces for fiber optic cable / at 100 Mbit/s	2
Design of the optical interface for fiber optic cable / at 100 Mbit/s	BFOC sockets (multimode up to 3 km)
Interfaces / for communication / integrated	
Number of 100 Mbit/s ST(BFOC) ports for multimode	2

Number of 100 Mbit/s SC ports	
• for multimode	0
Number of 1000 Mbit/s LC ports	
• for multimode	0
• for single mode (LD)	0

Interfaces / others

Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	On 6-pole terminal block
• for power supply	6-pole plug-in terminal block

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A
Number of digital inputs	8
Number of electrical connections / for digital input signals	2
Type of electrical connection / for digital input signals	4-pole plug-in terminal block
Signal voltage	
• for signal <0> / at DC	-30 ... +3 V
— Rated value	24 V
• for signal <1> / at DC	13 ... 30 V
— Rated value	24 V
Input current / at digital input	
• with signal <0> / maximum	0.008 mA
• for signal <1>	0.008 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external	18 ... 32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	T 1.6 A / 250 V
Consumed current / maximum	1 A
Active power loss	
• at DC / at 24 V	20 W

Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	217 mm
Height	161 mm
Depth	69 mm
Net weight	1.4 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	No
• S7-1500 rail mounting	No
• fixed-mounted	Yes

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $< \sim 0.3 \text{ s}$	50
Cascading in cases of star topology	any (depending only on signal propagation time)

Product functions / management, configuration

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• RMON	Yes
• Port mirroring	Yes
• multiport mirroring	No
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
Protocol / is supported	
• SNMP v1	Yes

Product functions / Diagnosis

Product function

- Statistics Packet Size
- Statistics packet type
- Error statistics

Yes
Yes
Yes

Product functions / DHCP

Product function

- DHCP client

Yes

Product functions / Redundancy

Product function

- Ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes
Yes
Yes
Yes

Product function

- media redundancy protocol (MRP) with redundancy manager

Yes

Product functions / Time

Product function

- SICLOCK support

Yes

Standards, specifications, approvals

Standard

- for FM
- for safety / from CSA and UL
- for emitted interference
- for interference immunity

FM3611: Class 1, Divison 2, Group A, B, C, D / T.. A, CL.1, Zone 2, GP. IIC, T4
UL 60950-1, CSA C22.2 No. 60950-1
EN 61000-6-4
EN 61000-6-2

Certificate of suitability

- CE marking
- C-Tick
- KC approval

Yes
Yes
No

Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)
- Bureau Veritas (BV)
- Det Norske Veritas (DNV)
- Germanische Lloyd (GL)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (NK)

Yes
Yes
Yes
Yes
Yes
Yes

- Polski Rejestr Statkow (PRS)

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

14.08.2015