

Product-type designation		CP 1613 A2
		COMMUNICATION PROCESSOR CP 1613 A2 PCI CARD (32BIT;33MHZ/66MHZ; 3.3V/5V UNIVERSAL KEY) FOR CONNECTION TO IND. ETHERNET (10/100MBIT/S) WITH ITP AND RJ 45 PORT VIA HARDNET-IE S7 AND S7-REDCONNECT. SUPPORT FOR OPERATING SYSTEM SEE SIMATIC NET SW
Transmission rate		
Transfer rate / at the interface 1		10 ... 100 Mbit/s
Interfaces		
Number of electrical connections		2
• at interface 1 / in accordance with Industrial Ethernet		
Design of electrical connection		RJ45 port / 15-pin ITP connection
• at interface 1 / in accordance with Industrial Ethernet		
Supply voltage, current consumption, power loss		
Type of / supply voltage		DC
Supply voltage		
• 1 / from backplane bus		5 V
• 2 / from the backplane bus		12 V
Relative symmetrical tolerance		
• at 5 V / with DC		5 %
• at 12 V / with DC		5 %
Consumed current		
• 1 / from backplane bus / with DC / maximum		0.45 A
• 2 / from backplane bus / with DC / maximum		0.5 A
Resistive loss		4 W
Permitted ambient conditions		

Ambient temperature	
• during operating	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP00
Design, dimensions and weight	
Module format	PCI
Width	21.6 mm
Height	107 mm
Depth	167 mm
Net weight	140 g
Product properties, functions, components / general	
Number of plug-in cards in the same design / can be plugged in / per PC station	4
Number of modules / note	-
Performance data	
Performance data / open communication	
Software / for open communication / by means of SEND/RECEIVE / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	120
Performance data / S7 communication	
Software / for S7 communication / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections	
• for S7/PG communication / maximum	120
• for optimized S7 communication / maximum	40
Performance data / multi-protocol mode	
Number of active connections / with multiprotocol mode	120
Number of configurable connections / per PC station	207
Performance data / PROFINET CBA	
Software / for PROFINET CBA communication / required	Yes, PN CBA OPC server
Number of remote connection partners / with PROFINET CBA	228
Number of connections / with PROFINET CBA / total	10000
Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	No
• DCP	Yes

Configuration software	
• for PROFINET CBA / required	Yes, SIMATIC iMAP
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / Redundancy	
Software / for redundancy function / required	Yes, HARDNET-IE S7-REDCONNECT for communication with SIMATIC S7 H systems
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported / NTP	No
Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / of CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Verification of suitability	
• CE mark	Yes
• C-Tick	Yes
Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. Version 3.4 – 14.11.2013-Siemens AG, I IA L CG, Nuremberg

letzte Änderung:

Jul 14, 2014