

Product-type designation

PROFIBUS OLM P22



PROFIBUS OLM/P22 V4.0;
OPTICAL LINK MODULE W. 2 RS485 AND 2 PLASTIC-FO-
INTERFACES (4 BFOC-SOCKETS);
WITH SIGNAL. CONTACT AND MEASURING OUTPUT;
INCL. 4 BFOC-CONNECTORS

Transmission rate

Transfer rate

• with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
• With PROFIBUS PA	45.45 kbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	4
Number of electrical connections	
• for network components and terminal equipment	2
• for measuring instrument	1 1
• for signaling contact	1
• for power supply	1
• for redundant power supply	1
Design of electrical connection	
• for network components and terminal equipment	9-pin Sub-D socket
• for measuring device	2-pole terminal block
• for power supply and signaling contact	5-pole terminal block
Number of optical interfaces / for optical waveguide	2
Design of the optical interface / for optical waveguide	BFOC port

Optical data

Damping ratio / of FOC transmission link	
• for POF FOC with 980/1000 µm / at 230 dB/km	13 dB
Signal delay time in bit time	6.5 bit
Injectable optical power relating to 1 mW	
• of FOC transmission link	
• for PCF FOC with 200/230 µm / at 10 dB/km	-17 dB
• for POF FOC with 980/1000 µm / at 230 dB/km	-5 dB
Wavelength	
• of FOC transmission link	
• for PCF FOC with 200/230 µm / at 10 dB/km	660 nm
• for POF FOC with 980/1000 µm / at 230 dB/km	660 nm
Cable length	
• for PCF FOC with 200/230 µm / at 10 dB/km / maximum	400 m
• for POF FOC with 980/1000 µm / at 230 dB/km / maximum	80 m
Signal-Inputs/outputs	
Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage / for DC	
• rated value	24 V
• minimum	18.8 V
• maximum	28.8 V
Product component / fusing at power supply input	Yes
Consumed current / At 24 V / with DC / maximum	0.2 A
Permitted ambient conditions	
Ambient temperature	
• during operating	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP40
Design, dimensions and weight	
Design	compact
Width	39.5 mm
Height	112 mm
Depth	74.5 mm
Net weight	340 g

Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
Product properties, functions, components / general	
Product function / Ring redundancy	Yes
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, EN60079-28: 2007, II 3 (2) G Ex nA [opis] IIC T4 KEMA 09 ATEX 0173X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 Nr. 60950-1
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213 -M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Verification of suitability	EN 61000-6-2, EN 61000-6-4
• CE mark	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
letzte Änderung:	Jun 16, 2014