



IE FC M12 PLUG PRO 2X2 M12 PLUG CONNECTOR W. RUGGED METAL HOUSING AND FC CONNECTING METHOD, WITH AXIAL CABLE OUTLET (D CODED) 1 PACKAGE = 1 PIECE FOR SCALANCE X208 PRO AND ET200 PRO PN

Transfer rate

• 1 / for Industrial Ethernet	10 Mbit/s
• 2 / for Industrial Ethernet	100 Mbit/s

Interfaces

Number of electrical connections

• for Industrial Ethernet FC TP cables	4
• for network components and terminal equipment	1

Design of the electrical connection / FastConnect

Yes

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width	19 mm
Height	19 mm
Depth	73 mm
Net weight	40 g

Permitted ambient conditions

Ambient temperature

• during operating	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C

Relative humidity

- at 25 °C / without condensation / during operating / maximum

95 %

Product properties, functions, components / general

Product feature / [not supplied - silicon-free]

Yes

Composant produit

- décharge de traction

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity
- UL-registration

Yes

Yes

letzte Änderung:

Jul 17, 2012