



IE FC M12 PLUG PRO 4X2 M12 CONNECTOR WITH RUGGED METAL HOUSING A. FC CONNECT.- METHOD, WITH AXIAL CABLE OUTLET (X-CODED) 1 PACKAGE = 1 PCE FOR SCALANCE W

Transfer rate

• 1 / for Industrial Ethernet	10 Mbit/s
• 2 / for Industrial Ethernet	100 Mbit/s
• 3 / for Industrial Ethernet	1000 Mbit/s

Interfaces

Number of electrical connections

• for Industrial Ethernet FC TP cables	8
• for network components and terminal equipment	1

Design of the electrical connection / FastConnect

Yes

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width	16 mm
Height	16 mm
Depth	53 mm
Net weight	40 g

Permitted ambient conditions

Ambient temperature

• during operating	-25 ... +85 °C
• during storage	-25 ... +85 °C
• during transport	-25 ... +85 °C

Product properties, functions, components / general

Product feature / [not supplied - silicon-free]

Yes

Composant produit

- décharge de traction

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity
- UL-registration

Yes

No

letzte Änderung:

Jul 17, 2012