

Product-type designation

IE M12 Panel Feedthrough PRO



IE M12 PANEL FEEDTHROUGH PRO;
CONTROL CABINET BUSHING FOR TRANSITION OF M12
(D-CODED) CONNECT. METHOD (IP65) ON M12 (D-
CODED) CONNECT. METHOD (IP65);
1 PACKAGE = 5 PCS

Transfer rate

- 1 / for Industrial Ethernet
- 2 / for Industrial Ethernet

10 Mbit/s

100 Mbit/s

Interfaces

Number of electrical connections

- for network components and terminal equipment

2

Design of the electrical connection / FastConnect

No

Mechanical data

Material / of the enclosure

metal

Design, dimensions and weight

Type of cable outlet

180 degree cable outlet

Width

35.6 mm

Height

22.6 mm

Depth

44.5 mm

Net weight

36 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

-5 ... +60 °C

-5 ... +60 °C

-5 ... +60 °C

Protection class IP

IP65/67 (M12) / IP65/67 (M12)

Product properties, functions, components / general

Product feature / silicon-free

Yes

Product component

- strain relief

Yes

Standards, specifications, approvals

Verification of suitability

- RoHS conformity
- UL-registration

Yes

No

Standard for structured cabling

Cat5

letzte Änderung:

Aug 6, 2014