

product type designation



Cu/FO Modular Outlet

Cu/FO modular outlet module support for mounting of IE RJ45 Keystone or FO LC coupler; mounting on DIN rail; 1 pack = 1 unit.

suitability for use

Module carrier for mounting up to 6 IE RJ45 Keystone (6GK19010BE100AA0) and / or FO LC Coupler (6GK19010RP100AA0) on a DIN rail

mechanical data

material / of the enclosure metal

design, dimensions and weights

width 61 mm
height 132 mm
depth 132 mm
net weight 700 g
fastening method
• 35 mm top hat DIN rail mounting Yes

ambient conditions

ambient temperature
• during operation -40 ... +70 °C
• during storage -40 ... +70 °C
• during transport -40 ... +70 °C
relative humidity / at 25 °C / without condensation / during operation / maximum 95 %
protection class IP IP20

product features, product functions, product components / general

product feature
• silicon-free Yes
product component / strain relief Yes

standards, specifications, approvals

certificate of suitability
• RoHS conformity Yes

further information / internet-Links

Internet-Link
• to website: Industrial communication <http://www.siemens.com/simatic-net>
• to website: Industry Mall <https://mall.industry.siemens.com>
• to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
• to website: Selection guide for cables and connectors <https://sie.ag/2QdlxcP>
• to website: Image database <http://automation.siemens.com/bilddb>
• to website: CAx-Download-Manager <http://www.siemens.com/cax>
• to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

12/15/2022