

Product-type designation

IE FC outlet RJ45



IE FC OUTLET RJ45 INDUSTRIAL ETHERNET
FASTCONNECT OUTLET RJ45 F. TRANSITION FROM IE
FC CABLES AND TP CORD PATCH CABLES

Electrical data

Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s

Interfaces

Number of electrical connections	
• for Industrial Ethernet FC TP cables	1
• for network components and terminal equipment	1
Design of the electrical connection	
• for Industrial Ethernet FC TP cables	integrated insulation displacement contacts
• FastConnect	Yes

Mechanical data

Material / of the enclosure	metal
Width	31.7 mm
Height	107 mm
Depth	30 mm
Net weight	300 g
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

-25 ... +70 °C

-40 ... +70 °C

-40 ... +70 °C

Protection class IP

IP20

Standards, specifications, approvals

Verification of suitability

- UL-registration

Yes

Standard for structured cabling

Cat5

Further Information / Internet Links

Internet-Link

- to website: Industry Mall
- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

letzte Änderung:

Aug 4, 2014