

Product-type designation

SpliT Connect Tap



PROFIBUS PA SPLITCONNECT TAP,
FOR ASSEMBLING OF PROFIBUS PA SEGMENTS AND
CONNECTION OF PA FIELD DEVICES,
INSULATION DISPLACEMENT TERMINAL,
IP67 PACK. UNIT: 10 PIECES = 1 PACK

Interfaces

Number of electrical connections

- for PROFIBUS cables

3

Design of the electrical connection

- for PROFIBUS cables

integrated insulation displacement contacts

Mechanical data

Material / of the enclosure

PBT (polybutyleneterephthalate)

Width

84 mm

Height

54 mm

Depth

49 mm

Net weight

170 g

Mounting type

- 35 mm DIN rail mounting
- wall mounting

Yes

Yes

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

-40 ... +85 °C

-40 ... +85 °C

-40 ... +85 °C

Protection class IP

IP67

Standards, specifications, approvals

Verification of suitability

- UL-registration

Yes

Further Information / Internet Links

Internet-Link

- to website: Industry Mall
- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

letzte Änderung:

Aug 4, 2014