

product type designation

Split Connect Coupler

PROFIBUS PA SplitConnect Coupler; Connection element for cascading SplitConnect TAPs for setting up neutral points; 1 pack = 10 units



| transfer rate                                                     |                                                                                                     |
|-------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| transfer rate                                                     |                                                                                                     |
| • with PROFIBUS PA                                                | 31.25 kbit/s                                                                                        |
| ambient conditions                                                |                                                                                                     |
| ambient temperature                                               |                                                                                                     |
| • during operation                                                | -40 ... +85 °C                                                                                      |
| • during storage                                                  | -40 ... +85 °C                                                                                      |
| • during transport                                                | -40 ... +85 °C                                                                                      |
| protection class IP                                               | IP67                                                                                                |
| product features, product functions, product components / general |                                                                                                     |
| product feature                                                   |                                                                                                     |
| • silicon-free                                                    | Yes                                                                                                 |
| further information / internet-Links                              |                                                                                                     |
| Internet-Link                                                     |                                                                                                     |
| • to website: Industrial communication                            | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                 |
| • to website: Industry Mall                                       | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                   |
| • to website: Information and Download Center                     | <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> |
| • to website: Image database                                      | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>             |
| • to website: CAX-Download-Manager                                | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                 |
| • to website: Industry Online Support                             | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>             |

last modified:

6/30/2021 