

Product type designation

SpliT Connect M12 Jack

PB PA SPLITCONNECT M12 JACK, CONNECT. ELEMENT FOR
FOR TERMINATING OF PROFIBUS PA FIELD DEVICES WITH
M12 INTERFACE TO PB FC PROCESS CABLE PACK. UNIT: 1
PACK= 5 PCS



Electrical data

Transfer rate / with PROFIBUS PA	31.25 kbit/s
----------------------------------	--------------

Interfaces

Number of electrical connections	1
• for PROFIBUS cables	
Type of electrical connection	integrated insulation displacement contacts
• for PROFIBUS cables	

Permitted ambient conditions

Ambient temperature	
• during operation	
• during storage	
• during transport	
Protection class IP	IP67

Further Information / Internet Links

Internet-Link	http://www.siemens.com/snst
• to website: Selector SIMATIC NET SELECTION TOOL	

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

29.02.2016