

Product-type designation		PB ECOFAST Hybrid Plug angled
		PROFIBUS ECOFAST HYBRID PLUG ANGLED (ECOFAST CU) 2 X CU; 4 X 1.5 SQMM CU; SOCKET CONNECTOR HANBRID PACK OF 5
Acceptability for application		For connection to ECOFAST hybrid cables, transmission of data and power
Transfer rate / with PROFIBUS		9.6 kbit/s ... 12 Mbit/s
Interfaces		
Number of electrical connections		
• for PROFIBUS cables		1
• for network components and terminal equipment		1
Design of the electrical connection		
• for PROFIBUS cables		Integrated crimp contacts for 6-core ECOFAST hybrid cables
• for network components and terminal equipment		Hanbrid connector with female insert
Design of the electrical connection / FastConnect		No
Mechanical data		
Material / of the enclosure		plastic
Design, dimensions and weight		
Type of cable outlet		90 degree cable outlet
Width		27 mm
Height		27 mm
Depth		71 mm
Net weight		40 g
Permitted ambient conditions		
Ambient temperature		
• during operating		-20 ... +70 °C
• during storage		-40 ... +80 °C
• during transport		-40 ... +80 °C
Protection class IP		IP65/67
Chemical resistance / to water		resistant
Product properties, functions, components / general		
Product feature / silicon-free		Yes
Product component		
• strain relief		Yes
Standards, specifications, approvals		

Verification of suitability

- RoHS conformity
- UL-registration

letzte Änderung:

Yes

No

Jul 28, 2014