

**Product-type designation** **7/8-inch Power T-Tap PRO**

7/8" POWER T-TAP PRO,  
ENERGY-T-CONNECTOR FOR ET200 WITH 2  
7/8" SOCKET INSERTS AND ONE 7/8" PIN INSERT,  
5 PIECES PER PACKAGING UNIT



Acceptability for application

For power connection and distribution to ET200pro modules

**Interfaces**

|   |  |
|---|--|
| Number of electrical connections  | 3  |
| <ul style="list-style-type: none"> <li>• for network components and terminal equipment</li> </ul> |  |
| Design of the electrical connection   | 7/8 inch plug (2 x female insert, 1 x male insert) |
| <ul style="list-style-type: none"> <li>• for network components and terminal equipment</li> </ul> |  |
| Design of the electrical connection / FastConnect   | No   |

**Mechanical data**

|                             |       |
|-----------------------------|-------|
| Material / of the enclosure | metal |
|-----------------------------|-------|

**Design, dimensions and weight**

|            |         |
|------------|---------|
| Width      | 58.5 mm |
| Height     | 73.5 mm |
| Depth      | 26.5 mm |
| Net weight | 112 g   |

**Permitted ambient conditions**

|  |                |
|--|----------------|
| Ambient temperature  |                |
| <ul style="list-style-type: none"> <li>• during operating</li> </ul> | -40 ... +70 °C |
| <ul style="list-style-type: none"> <li>• during storage</li> </ul>   | -40 ... +80 °C |
| <ul style="list-style-type: none"> <li>• during transport</li> </ul> | -40 ... +80 °C |
| Protection class IP  | IP65/67        |

Chemical resistance / to water

resistant

### Product properties, functions, components / general

Product feature / silicon-free

Yes

Product component

- strain relief

Yes

### Standards, specifications, approvals

Verification of suitability

- RoHS conformity
- UL-registration

Yes

No

**letzte Änderung:**

Jul 28, 2014