

Product-type designation

Power Plug PRO (Push Pull)



POWER PLUG PRO,
5-POLE PUSH PULL POWER PLUG FOR ON-SITE
MOUNTING (PACKAGING UNIT: 1 PLUG)

Acceptability for application

Field-assembly connector for push-pull device connection in high degree of protection, for voltage supply with 2 x 24 V DC

Interfaces

Number of electrical connections

- for network components and terminal equipment

1

Design of the electrical connection

- for PROFIBUS cables
- for network components and terminal equipment

Integrated spring-loaded contacts for 5-core energy cables
Power contacts (Push Pull casing)

Design of the electrical connection / FastConnect

No

Mechanical data

Material / of the enclosure

plastic

Design, dimensions and weight

Type of cable outlet

180 degree cable outlet

Width

36 mm

Height

30 mm

Depth

66.3 mm

Net weight

83.1 g

Permitted ambient conditions

Ambient temperature

- during operating

-40 ... +70 °C

• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP65/67
Chemical resistance / to water	resistant
Product properties, functions, components / general	
Product feature / silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
letzte Änderung:	Jul 28, 2014