

Product type designation
Product description

Power Plug PRO (Push Pull)
Power connector, 5-pole
Power Plug PRO 5-pole Push Pull Power connector with Metal
housing for on-site mounting (Packaging unit 1 connector)



Suitability for use	Field-assembly connector (spring-loaded contacts for 5-core power lines) for push-pull device connection in high degree of protection, for voltage supply with 2 x 24 V DC (metal housing)
---------------------	--

Interfaces

Number of electrical connections	1
• for network components or terminal equipment	
Type of electrical connection	Power contacts (Push Pull casing)
• for network components or terminal equipment	
Type of electrical connection / FastConnect	No

Mechanical data

Material / of the enclosure	metal
Locking mechanism design	Push-pull

Design, dimensions and weights

Type of cable outlet	180° cable outlet
Width	36 mm
Height	30 mm
Depth	66.3 mm

Net weight	83.1 g
Ambient conditions	
Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Chemical resistance	
• to water	resistant
Protection class IP	IP65/67
Product features, product functions, product components / general	
Product feature	
• silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
• Railway application in accordance with EN 50155	No
Further information / Internet-Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	12/17/2019