SIEMENS

Product data sheet

6GK1908-0DC10-6AA3

Product-type designation

Signalling Contact M12 Cable Connector

SIGNALLING CONTACT M12 CABLE CONNECTOR PRO, SOCKET FOR CONNECTION OF SCALANCE X208PRO FOR SIGN.CONTACT; W. MOUNTING INSTR. 5-POLE, B-CODED, 3 PCS



Acceptability for application

For connection to SCALANCE X208PRO for signaling contact

Integrated screw contacts for 2-core power cables

M12 connector (B-coded, 5-pin)

180 degree cable outlet

Interfaces

Number of electrical connections

for network components and terminal equipment

Design of the electrical connection

• for PROFIBUS cables

• for network components and terminal equipment

Design of the electrical connection / FastConnect

Mechanical data

Type of cable outlet

Depth

Material / of the enclosure plastic

Design, dimensions and weight

Width 14 mm
Height 14 mm

Net weight

Permitted ambient conditions

Ambient temperature

• during operating -40 ... +70 °C

• during storage -40 ... +80 °C

1

No

59 mm

37 g

during transport	-40 +80 °C
Protection class IP	IP65/67
Chemical resistance / to water	resistant
Product properties, functions, components / general	
Product feature / silicon-free	Yes
Product component	
• strain relief	Yes
Standards, specifications, approvals	
Verification of suitability	
RoHS conformity	Yes
UL-registration	No
letzte Änderung:	Jul 28, 2014