

Product type designation

SCALANCE X101-1AUI



SCALANCE X101-1AUI IE MEDIA CONVERTER
UNMANAGED 1 X 10MBIT/S RJ45 PORT,
1 X 10MBIT/S AUI SEGMENT PORT,
LED DIAGNOSIS,
FAULT SIGNAL. CONTACT WITH SET BUTTON,
REDUNDANT POWER SUPPLY,
PROFINET COMPLIANT SLEEVE INCL. ELECTRONIC
MANUAL ON CD

Transmission rate

• 1	10 Mbit/s
Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
• for network components and terminal equipment	2
• for signaling contact	1
• for power supply	1
• for redundant power supply	1
Design of electrical connection	
• for network components and terminal equipment	RJ45 port, 15-pin D-sub socket
• for signaling contact	2-pole terminal block
Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Type of / supply voltage	DC
Supply voltage / external	24 V
• minimum	18 V
• maximum	32 V
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	1 A / 33 V

Consumed current / maximum	0.16 A
Active power loss / at 24 V / for DC	3 W
Ambient temperature	
• during operating	-10 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP30
Design	Compact
Width	40 mm
Height	125 mm
Depth	124 mm
Net weight	0.56 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes
Standard	
• for EMC / from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T.., Class 1, Zone 2, Group IIC, T..
• for hazardous zone	EN 60079-15 II 3 G EEx nA II T.. KEMA 06 ATEX 0021 X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T..
• for emitted interference	EN 61000-6-4:2001
• for interference immunity	EN 61000-6-4:2001
Verification of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	No
Further Information / Internet Links	
Internet-Link	

- to website: Industry Mall
- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

letzte Änderung:

<http://www.siemens.com/industrial-controls/mall>
<http://www.siemens.com/snst>
<http://www.siemens.com/simatic-net>
<http://www.siemens.com/automation/net/catalog>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<http://support.automation.siemens.com>

Jul 21, 2014