## 6GK5102-1GS00-2AC2





SCALANCE XCM102, IE media converter unmanaged 1x 100/1000 Mbps RJ45 port, 1x 100/1000 Mbps SFP port, LED diagnostics, error signaling contact with set pushbutton redundant power supply, securing collar, manual available as a download .

transfer rate	
transfer rate	100 Mbit/s, 1000 Mbit/s
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum number of electrical connections	2
<ul> <li>for network components or terminal equipment</li> </ul>	1
for signaling contact	1
• for power supply	1
for redundant voltage supply	1
type of electrical connection	
<ul> <li>for network components or terminal equipment</li> </ul>	RJ45 port
<ul> <li>for signaling contact</li> </ul>	2-pole terminal block
for power supply	2x 3-pole terminal block
signal inputs/outputs	
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
supply voltage / 1 / rated value	24 V
<ul> <li>type of voltage / 1 / of the supply voltage</li> </ul>	DC
<ul> <li>consumed current / 1 / at rated supply voltage / maximum</li> </ul>	0.15 A
<ul><li>power loss [W] / 1 / rated value</li></ul>	2.5 W
supply voltage / 2 / rated value	24 V
<ul> <li>consumed current / 2 / at rated supply voltage / maximum</li> </ul>	0.3 A
<ul><li>power loss [W] / 2 / rated value</li></ul>	5 W
product component / fusing at power supply input	Yes
ambient conditions	
ambient temperature	
<ul><li>during operation</li></ul>	-40 +70 °C
during storage	-40 +85 °C
<ul> <li>during transport</li> </ul>	-40 +85 °C
• note	max. operating temperature dependent on the use of SFP plug-in transceiver
relative humidity / at 25 $^{\circ}\text{C}$ / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Compact

width 35 mm height 147 mm depth 123 mm net weight 0.22 kg fastening method • 35 mm top hat DIN rail mounting Yes • S7-300 rail mounting Yes · wall mounting Yes standards, specifications, approvals certificate of suitability • CE marking Yes **MTBF** 152 a further information / internet-Links Internet-Link • to website: Industrial communication http://www.siemens.com/simatic-net • to website: Industry Mall https://mall.industry.siemens.com • to website: Information and Download Center http://www.siemens.com/industry/infocenter • to website: Image database http://automation.siemens.com/bilddb • to website: CAx-Download-Manager http://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com security information Siemens provides products and solutions with industrial security security information functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this inmind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter.

last modified:

2/3/2023

(V3.4)

For more information, visit http://support.automation.siemens.com.