

Product-type designation

SCALANCE X108



SCALANCE X108, UNMANAGED IE SWITCH,
8 X 10/100MBIT/S RJ45 PORTS,
LED DIAGNOSTICS,
FAULT SIGNAL. CONTACT WITH SET BUTTON,
REDUNDANT VOLTAGE SUPPLY,
WITH ELECTRONIC MANUALS ON CD

Transmission rate

Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	8
Number of electrical connections	
• for network components and terminal equipment	8
• for signaling contact	1
• for power supply	1
• for redundant power supply	1
Design of electrical connection	
• for network components and terminal equipment	RJ45 port
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block

Signal-Inputs/outputs

Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A

Supply voltage, current consumption, power loss

Type of / supply voltage	DC
--------------------------	----

Supply voltage / external	24 V
• minimum	18 V
• maximum	32 V
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	0,6 A / 60 V
Consumed current / maximum	0.14 A
Active power loss / at 24 V / for DC	3.36 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-20 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP30
Design, dimensions and weight	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.78 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes
Standards, specifications, approvals	
Standard	
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T..., Class 1 / Zone 2 / Group IIC / T..
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Verification of suitability	EN 61000-6-2, EN 61000-6-4
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
• E1 approval	Yes
• e1 approval	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes

• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes

Further Information / Internet Links

Internet-Link

• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. Version 3.4 – 14.11.2013- Siemens AG, I I A L C G, Nuremberg

letzte Änderung:

Jun 16, 2014