

Product type designation

SCALANCE XC124

SCALANCE XC124, UNMANAGED IE SWITCH, 24 X 10/100MBIT/S RJ45 PORTS, LED-DIAGNOSIS, FAULT SIGNAL CONTACT WITH SET BUTTON, REDUNDANT POWER SUPPLY MANUAL AVAILABLE AS DOWNLOAD



Transmission rate

Transfer rate	10 Mbit/s, 100 Mbit/s
---------------	-----------------------

Interfaces / for communication / integrated

Number of electrical connections	
• for network components or terminal equipment	24; RJ45

Interfaces / others

Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	

- at DC / maximum

0.1 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external	9.6 ... 31.2 V
Supply voltage / 1 / Rated value	12 V
• Supply voltage / 1 / rated value	9.6 ... 31.2 V
• Type of voltage / 1 / of the supply voltage	DC
• Consumed current / 1 / at rated supply voltage / maximum	0.65 A
Supply voltage / 2 / Rated value	24 V
• Supply voltage / 2 / rated value	9.6 ... 31.2 V
• Type of voltage / 2 / of the supply voltage	DC
• Consumed current / 2 / at rated supply voltage / maximum	0.325 A
• Power loss [W] / 2 / Rated value	7.8 W
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	2.5 A / 125 V
Power loss [W]	
• at DC / at 24 V	7.8 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	compact
Width	120 mm
Height	147 mm
Depth	125 mm
Net weight	0.85 kg
Material / of the enclosure	Polycarbonate (PC-GF10)
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes

- S7-1500 rail mounting

Yes

Product properties, functions, components / general

Number of automatically learnable MAC addresses 2048

Product functions / management, configuration

Product function

- multiport mirroring
- CoS
- switch-managed

No

Yes

No

Product functions / Redundancy

Product function

- Parallel Redundancy Protocol (PRP)/operation in the PRP-network
- Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)

Yes

No

Standards, specifications, approvals

Standard

- for hazardous zone
- for safety / from CSA and UL
- for hazardous zone / from CSA and UL
- for emitted interference

EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010

UL 60950-1, CSA C22.2 No. 60950-1

UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T..

EN 61000-6-4 (Class B)

Certificate of suitability / CE marking

Yes

Laser protection class

LED Class 1

Certificate of suitability

- C-Tick
- E1 approval
- EC declaration of conformity EN 61010, IEC 61010-1, UL 61010A-1
- KC approval

EN 61000-6-2, EN 61000-6-4

Yes

No

Yes

Yes

MTBF / at 40 °C

58.42 y

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAX Download Manager

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

03/09/2017