



SCALANCE X204RNA EEC; redundant network access 2x 100 Mbit/s RJ45 ports; 2x 100 Mbit/s combo ports; LED diagnostics; error signaling contact with set button; simple power supply; network management; incl. electronic manual on CD-ROM, C-plug optional for PRP network

Product type designation	SCALANCE X204RNA EEC
Transfer rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / Integrated	
Number of electrical connections	
• for network components or terminal equipment	2
Number of combo ports / with RJ45 interface for optical plug-in transceiver	2
Interfaces / other	
Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	3-pole terminal block
• for power supply	3-pole terminal block
design of the removable storage	
• C-PLUG	Yes

Signal inputs/outputs

Operating voltage / of the signaling contacts	
• at AC / Rated value	230 V
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at AC / maximum	0.1 A
• at DC / maximum	0.1 A

Supply voltage, current consumption, power loss

Supply voltage	
• at AC	230 V
• at AC / rated value	85 ... 276 V
Supply voltage / 2 / Rated value	
• Type of voltage / 2 / of the supply voltage	DC
Supply voltage / at DC	24 V
• rated value	19.2 ... 300 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	1.25 A
Consumed current / maximum	0.25 A
Power loss [W]	
• at DC / at 24 V	6 W

Ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• Note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weights

Design	compact
Width	70 mm
Height	147 mm
Depth	123 mm
Net weight	0.78 kg
Product feature / conformal coating	Yes
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	No

- S7-300 rail mounting
- S7-1500 rail mounting

No

No

Product functions / management, configuration, engineering

Product function

- CLI
- web-based management
- MIB support
- TRAPs via email
- Configuration with STEP 7
- Port mirroring
- multiport mirroring
- with IRT / PROFINET IO switch
- PROFINET IO diagnosis

Yes

Yes

Yes

Yes

No

No

No

No

No

Product function / switch-managed

No

Protocol / is supported

- Telnet
- HTTP
- HTTPS
- TFTP
- FTP
- BOOTP
- GMRP
- DCP
- LLDP
- SNMP v1
- SNMP v2
- SNMP v3
- IGMP (snooping/querier)

No

Yes

Yes

No

No

No

No

Yes

No

Yes

Yes

Yes

No

Identification & maintenance function

- I&M0 - device-specific information
- I&M1 – higher-level designation/location designation

Yes

Yes

Product functions / Diagnostics

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics

Yes

Yes

Yes

Yes

Product functions / redundancy

Product function

• Ring redundancy	No
• High Speed Redundancy Protocol (HRP)	No
• high speed redundancy protocol (HRP) with redundancy manager	No
• high speed redundancy protocol (HRP) with standby redundancy	No
Protocol / is supported / Media Redundancy Protocol (MRP)	No
Product function	
• media redundancy protocol (MRP) with redundancy manager	No
• High-availability Seamless Redundancy (HSR)	No
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	Yes
• High-availability Seamless Redundancy (HSR) and Parallel Redundancy Protocol (PRP) coupling	No
• Passive listening	No

Product functions / Security

Protocol / is supported	
• SSH	Yes

Product functions / time

Product function	
• SICLOCK support	No
Protocol / is supported	
• NTP	No
• SNTP	Yes

Standards, specifications, approvals

Standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X
• for safety / from CSA and UL	UL 508, CSA C22.2 No. 142-M1987
• for emitted interference	EN 61000-6-4:2001 (Class A)
• for interference immunity	EN 61000-6-4:2001
MTBF	67.64 y

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Standard	
• for EMC	IEC 61850, IEEE 1613

Standards, specifications, approvals / other

Certificate of suitability	EN 61000-6-4:2001
• C-Tick	Yes
• Railway application in accordance with EN 50155	Yes
• Railway application in accordance with EN 50121-4	Yes
• Railway application in accordance with EN 50124-1	No
• Fire protection in accordance with EN 45545-2	Yes
• IEC 61850-3	Yes
• IEEE 1613	Yes
• KC approval	Yes

Standards, specifications, approvals / marine classification

Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• DNV GL	Yes
• Korean Register of Shipping (KRS)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes
• Royal Institution of Naval Architects (RINA)	Yes

accessories

Product extension / optional / C-PLUG	Yes
---------------------------------------	-----

Further information / Internet-Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

07/08/2020