

### Product type designation

Product description

### SCALANCE XB205-3

Preset for PROFINET mode!

SCALANCE XB205-3 MANAGEABLE LAYER 2 IE-SWITCH 5X 10/100 MBITS/S RJ45 PORTS 3X MM FO SC-PORT 1X CONSOLE PORT DIAGNOSTICS-LED REDUNDANT POWER SUPPLY TEMP.-RANGE 0 DGR C UP TO +60 DGR C; DIN RAIL MOUNTING PROFINET IO-DEVICE ETHERNET/IP CERTIFICATE DEFAULT PROFINET



### Transmission rate

Transfer rate	10 Mbit/s, 100 Mbit/s
---------------	-----------------------

### Interfaces / for communication / integrated

Number of electrical connections	
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	5
Number of 100 Mbit/s SC ports	
<ul style="list-style-type: none"> <li>for multimode</li> </ul>	3

### Interfaces / others

Number of electrical connections	
<ul style="list-style-type: none"> <li>for operator console</li> </ul>	1
<ul style="list-style-type: none"> <li>for management purposes</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
<ul style="list-style-type: none"> <li>for redundant voltage supply</li> </ul>	1
Type of electrical connection	
<ul style="list-style-type: none"> <li>for operator console</li> </ul>	RJ11 port
<ul style="list-style-type: none"> <li>for management purposes</li> </ul>	RJ45 port

- for power supply

6-pole terminal block

### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
<ul style="list-style-type: none"> <li>• external</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• external</li> </ul>	19.2 ... 28.8 V
Product component / fusing at power supply input	Yes
Consumed current / maximum	0.3 A

### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +70 °C
Relative humidity	
<ul style="list-style-type: none"> <li>• at 25 °C / without condensation / during operation / maximum</li> </ul>	96 %
Protection class IP	IP20

### Design, dimensions and weight

Design	compact
Width	80 mm
Height	117 mm
Depth	109 mm
Net weight	0.35 kg
Material / of the enclosure	Plastic
Mounting type	
<ul style="list-style-type: none"> <li>• 35 mm DIN rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	No
<ul style="list-style-type: none"> <li>• S7-1500 rail mounting</li> </ul>	No

### Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $<\sim 0.3\sim$ s	50
Cascading in cases of star topology	any (depending only on signal propagation time)

### Product functions / management, configuration

Product function	
<ul style="list-style-type: none"> <li>• CLI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• web-based management</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• MIB support</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TRAPs via email</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Configuration with STEP 7</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• RMON</li> </ul>	Yes

<ul style="list-style-type: none"> <li>• Port mirroring</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• multiport mirroring</li> </ul>	No
<ul style="list-style-type: none"> <li>• CoS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• with IRT / PROFINET IO switch</li> </ul>	No
<ul style="list-style-type: none"> <li>• PROFINET IO diagnosis</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• switch-managed</li> </ul>	Yes
Telegram length / for Ethernet / maximum	1522 byte
Protocol / is supported	
<ul style="list-style-type: none"> <li>• Telnet</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• HTTPS</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• TFTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• FTP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• BOOTP</li> </ul>	No
<ul style="list-style-type: none"> <li>• DCP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• LLDP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• EtherNet/IP</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IGMP (snooping/querier)</li> </ul>	Yes
Identification & maintenance function	
<ul style="list-style-type: none"> <li>• I&amp;M0 - device-specific information</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• I&amp;M1 – higher-level designation/location designation</li> </ul>	Yes
Protocol / is supported	
<ul style="list-style-type: none"> <li>• SNMP v1</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v2</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SNMP v3</li> </ul>	Yes
<b>Product functions / Diagnosis</b>	
Product function	
<ul style="list-style-type: none"> <li>• Port diagnostics</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Statistics Packet Size</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Statistics packet type</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Error statistics</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• SysLog</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• loopback diagnostics</li> </ul>	Yes
<b>Product functions / VLAN</b>	
Product function	
<ul style="list-style-type: none"> <li>• VLAN - port based</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• VLAN - protocol-based</li> </ul>	No
<ul style="list-style-type: none"> <li>• VLAN - IP-based</li> </ul>	No
<ul style="list-style-type: none"> <li>• VLAN dynamic</li> </ul>	No

## Product functions / DHCP

### Product function

- DHCP client Yes

## Product functions / Redundancy

### Product function

- Ring redundancy Yes
- High Speed Redundancy Protocol (HRP) Yes
- high speed redundancy protocol (HRP) with redundancy manager Yes
- high speed redundancy protocol (HRP) with standby redundancy No

Protocol / is supported / Media Redundancy Protocol (MRP) Yes

### Product function

- media redundancy protocol (MRP) with redundancy manager Yes
- redundancy procedure STP Yes
- redundancy procedure RSTP Yes
- redundancy procedure MSTP Yes
- Parallel Redundancy Protocol (PRP)/operation in the PRP-network No
- Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) No
- Passive listening Yes

## Product functions / Security

### Product function

- IEEE 802.1x (radius) Yes
- Broadcast/Multicast/Unicast Limiter Yes
- broadcast blocking Yes

### Protocol / is supported

- SSH Yes

## Product functions / Time

### Product function

- SICLOCK support Yes

### Protocol / is supported

- NTP Yes
- SNTP Yes

## Standards, specifications, approvals

### Standard

- for FM FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T5

<ul style="list-style-type: none"> <li>• for hazardous zone</li> </ul>	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-2
<ul style="list-style-type: none"> <li>• for hazardous zone / from CSA and UL</li> </ul>	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T5
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-3
Certificate of suitability / CE marking	Yes
Certificate of suitability	EN 61000-6-2, EN 61000-6-5
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50155</li> </ul>	No
<ul style="list-style-type: none"> <li>• Railway application in accordance with EN 50124-1</li> </ul>	No
<ul style="list-style-type: none"> <li>• KC approval</li> </ul>	Yes

### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAx Download Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

### Security information

Security information	<p>Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a>. (V3.4)</p>
----------------------	---

**last modified:**

07/07/2016