



SCALANCE XF206-1, flat, Managed IE switch, 6x 10/100 Mbit/s RJ45 ports, 1x 100 Mbit/s FO port, Error signaling contact with set button, Redundant power supply, PROFINET IO device, network management, Redundancy Manager integrated, incl. electron. manual on CD-ROM, C-plug optional

Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections • for network components or terminal equipment	6
Number of 100 Mbit/s ST(BFOC) ports • for multimode	1
Number of 100 Mbit/s SC ports • for multimode	0
Number of 1000 Mbit/s LC ports • for multimode • for single mode (LD)	0 0
Interfaces / others	
Number of electrical connections • for signaling contact • for power supply • for redundant voltage supply	1 1 1
Type of electrical connection	

• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
design of the removable storage	
• C-PLUG	Yes

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external / minimum	18 V
• external / maximum	32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	1.1 A / 33 V
Consumed current / maximum	0.17 A
Power loss [W]	
• at DC / at 24 V	4.08 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
• Note	If the IE switch XF 200 is installed horizontally a maximum ambient temperature of +40 °C is permitted
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	Flat
Width	75 mm
Height	125 mm
Depth	73 mm
Net weight	0.25 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	No
• S7-300 rail mounting	No

- S7-1500 rail mounting

No

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $< \sim 0.3 \text{ s}$

100

Cascading in cases of star topology

any (depending only on signal propagation time)

Product functions / management, configuration

Product function

- CLI
- web-based management
- MIB support
- TRAPs via email
- Configuration with STEP 7
- Port mirroring
- multiport mirroring
- with IRT / PROFINET IO switch
- PROFINET IO diagnosis
- switch-managed

Yes
Yes
Yes
Yes
Yes
Yes
No
No
Yes
Yes

Protocol / is supported

- Telnet
- HTTP
- HTTPS
- TFTP
- FTP
- BOOTP
- DCP
- LLDP
- SNMP v1
- SNMP v2
- SNMP v3

Yes
Yes
Yes
Yes
Yes
No
Yes
Yes
Yes
Yes
Yes

Identification & maintenance function

- I&M0 - device-specific information
- I&M1 – higher-level designation/location designation

Yes
Yes

Product functions / Diagnosis

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics

Yes
Yes
Yes
Yes

Product functions / DHCP

Product function	
• DHCP client	Yes
Product functions / Redundancy	
Product function	
• Ring redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• high speed redundancy protocol (HRP) with redundancy manager	Yes
• high speed redundancy protocol (HRP) with standby redundancy	No
Protocol / is supported / Media Redundancy Protocol (MRP)	Yes
Product function	
• media redundancy protocol (MRP) with redundancy manager	Yes
• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
• Passive listening	Yes
Product functions / Security	
Protocol / is supported	
• SSH	Yes
Product functions / Time	
Product function	
• SICLOCK support	Yes
Protocol / is supported	
• NTP	No
• SNTP	Yes
Standards, specifications, approvals	
Standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 (2) G Ex nA [op is] IIC T4, KEMA 07 ATEX 0145 X
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous zone / from CSA and UL	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4
• for emitted interference	EN 61000-6-4:2001 (Class A)
• for interference immunity	EN 61000-6-2:2001
Standards, specifications, approvals / CE	
Certificate of suitability / CE marking	Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
• C-Tick	Yes
• Railway application in accordance with EN 50155	No
• Railway application in accordance with EN 50124-1	No
• KC approval	Yes

Standards, specifications, approvals / ship classification

Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• DNV GL	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	Yes
• Royal Institution of Naval Architects (RINA)	Yes

Standards, specifications, approvals / product conformity

MTBF / at 40 °C	43.52 y
-----------------	---------

Accessories

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

02/09/2018