



SCALANCE XC206-2 MANAGEABLE LAYER 2 IE-SWITCH; 6X 10/100 MBIT/S RJ45 PORTS; 2X 100 MBIT/S ST/BFOC-PORTS; 1X CONSOLE PORT; DIAGNOSTICS-LED; RREDUNDANT POWER SUPPLY; TEMP RANGE -40°C UP TO +70°C; MOUNTING WALL/ DINRAIL, S7 DINRAIL C-PLUG SLOT; REDUNDANCY FUNCTIONS; OFFICE FEATURES(RSTP,VLAN,...); PROFINET IO-DEVICE; ETHERNET/IP-CONFORMAL;

Transmission rate

Transfer rate	10 Mbit/s, 100 Mbit/s
---------------	-----------------------

Interfaces / for communication / integrated

Number of electrical connections	
• for network components or terminal equipment	6; RJ45
Number of 10/100 Mbit/s RJ45 ports / Integrated	
• with securing collar	6
Number of 100 Mbit/s ST(BFOC) ports	
• for multimode	2

Interfaces / others

Number of electrical connections	
• for operator console	1
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for operator console	RJ11
• for signaling contact	2-pole terminal block

• for power supply	4-pole terminal block
design of the removable storage	
• C-PLUG	Yes

Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external / minimum	9.6 V
• external / maximum	31.2 V
Supply voltage / 4 / Rated value	
• Consumed current / 4 / at rated supply voltage / maximum	0.25 A
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	2.5 A / 125 V
Consumed current / maximum	0.5 A
Power loss [W]	
• at DC / at 24 V	6 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Design	compact
Width	60 mm
Height	147 mm
Depth	125 mm
Net weight	0.54 kg
Material / of the enclosure	Polycarbonate (PC-GF10) / pressure die cast aluminum
Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

- S7-300 rail mounting
- S7-1500 rail mounting

Yes
Yes

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $< \sim 0.3 \sim s$	50
Cascading in cases of star topology	any (depending only on signal propagation time)
Product function / QoS according to DSCP	Yes
Product feature	
• Cut Through switching method	No
• Store & Forward switching method	Yes

Product functions / management, configuration

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• SMTP server	No
• Port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
Telegram length / for Ethernet / maximum	1632 byte
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• BOOTP	No
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
• EtherNet/IP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes

- I&M1 – higher-level designation/location designation

Yes

Product functions / Diagnosis

Product function

- Port diagnostics
- Statistics Packet Size
- Statistics packet type
- Error statistics
- SysLog

Yes

Yes

Yes

Yes

Yes

Product functions / VLAN

Product function

- VLAN - port based
- VLAN - protocol-based
- VLAN - IP-based
- VLAN dynamic

Yes

No

No

Yes

Number of VLANs / maximum

257

Number of VLANs - dynamic / maximum

257

Protocol / is supported / GVRP

Yes

Product functions / DHCP

Product function

- DHCP server
- DHCP client
- DHCP Option 82
- DHCP Option 66
- DHCP Option 67

Yes

Yes

Yes

Yes

Yes

Product functions / Redundancy

Product function

- Ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes

Yes

Yes

Yes

Protocol / is supported / Media Redundancy Protocol (MRP)

Yes

Product function

- media redundancy protocol (MRP) with redundancy manager
- redundancy procedure STP
- redundancy procedure RSTP
- redundancy procedure MSTP

Yes

Yes

Yes

Yes

• Parallel Redundancy Protocol (PRP)/operation in the PRP-network	No
• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
• Passive listening	Yes
Protocol / is supported	
• LACP	Yes

Product functions / Security

Product function	
• IEEE 802.1x (radius)	Yes
• Broadcast/Multicast/Unicast Limiter	Yes
• broadcast blocking	Yes
Protocol / is supported	
• SSH	Yes
• SSL	Yes

Product functions / Time

Product function	
• SICLOCK support	Yes
• NTP-client	Yes
• SNTP client	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes

Standards, specifications, approvals / CE

Certificate of suitability / CE marking	Yes
Product conformity / according to EMC-guideline	2014/30/EU
Standard	
• for EMC interference emission	EN 61000-6-4, EN 50121-4
• for immunity to EMI	EN 61000-6-2, EN 50121-4
Certificate of suitability / RoHS conformity	Yes; 2011/65/EU

Standards, specifications, approvals / hazardous environments

Certificate of suitability	
• ATEX	Yes
• IECEX	Yes
• FM registration	Yes

Standards, specifications, approvals / miscellaneous

Certificate of suitability	
• Railway application in accordance with EN 50121-4	Yes
• Regulatory Compliance Mark (RCM)	Yes

- EAC approval

Yes

Standards, specifications, approvals / product conformity

MTBF / at 40 °C

46.43 y

Accessories

Product extension / optional / C-PLUG

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/14/2017