

Product-type designation		SCALANCE X307-3
		SCALANCE X307-3, MANAGED PLUS IE SWITCH, 3 X 1000MBIT/S MM SC AND 7 X 10/100MBIT/S RJ45 PORTS, LED DIAGNOSTICS, FAULT SIGNAL. CONTACT WITH SELECT/SET BUTTON, PROFINET-IO DEVICE, NETWORK MANAGEMENT, INTEGRATED REDUNDANCY MANAGER, OFFICE FEATURES (RSTP, VLAN, IGMP,..) C-PLUG IN SCOPE OF SUPPLY
Transmission rate		
Transfer rate / 1		10 Mbit/s
Transfer rate / 2		100 Mbit/s
Transfer rate / 3		1000 Mbit/s
Interfaces		
Number of electrical/optical connections / for network components or terminal equipment / maximum		10
Number of electrical connections		
• for network components and terminal equipment		7
• for signaling contact		1
• for power supply		1
• for redundant power supply		2
Design of electrical connection		
• for network components and terminal equipment		RJ45 port
• for signaling contact		2-pole terminal block
• for power supply		4-pole terminal block
Number of optical interfaces / for optical waveguide		
• at 1000 Mbit/s		3
Design of optical interface / for optical waveguide		
• at 1000 Mbit/s		SC port (multimode up to 0.75 km)

Connectable optical power relative to 1 mW	
• of the transmitter output	-9.5 ... -4 dB
• of the receiver input / maximum	-3 dB
Optical sensitivity relative to 1 mW / of the receiver input / minimum	-17 dB
Attenuation / of fiber-optic cable transmission link / minimum necessary	0 dB
Range / at the optical interface / depending on the optical fiber used	0 ... 0.75 km
design of the removable storage / C-PLUG	Yes
Signal-Inputs/outputs	
Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of supply voltage / redundant power supply unit	No
Type of / supply voltage	DC
Supply voltage	
• external	24 V
• external	18 ... 32 V
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	F 3 A / 32 V
Consumed current / maximum	0.4 A
Power loss	
• at 24 V / for DC	9.6 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-10 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP30
Design, dimensions and weight	
Design	compact
Width	120 mm
Height	125 mm
Depth	123 mm
Net weight	1.4 kg
Mounting type	
• 19-inch installation	No
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes

• S7-300 rail mounting	Yes
Mounting type	When used in shipbuilding, installation on a 35 mm standard mounting rail is not permitted.

Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of <1-0.3\~s	50
Cascading in cases of star structuring	Any (depending only on signal propagation time)
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• Port mirroring	Yes
• multiport mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes

Product functions / Diagnosis

Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes

• Statistics packet type	Yes
• Error statistics	Yes
• SysLog	Yes
Product functions / VLAN	
Product function	
• VLAN - port based	Yes
• VLAN dynamic	Yes
Number of VLANs / maximum	255
Number of VLANs - dynamic / maximum	255
Protocol / is supported / GVRP	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes
Product functions / Redundancy	
Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes
• Standby redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• Media Redundancy Protocol (MRP)	Yes
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Passive listening	Yes
Protocol / is supported	
• STP/RSTP	Yes
• STP	Yes
• RSTP	Yes
• RSTP big network support	Yes
• LACP	Yes
Product functions / Security	
Product function	
• ACL - port/MAC-based	Yes
• IEEE 802.1X (radius)	Yes
• Broadcast/Multicast/Unicast Limiter	Yes
• broadcast blocking	Yes

Protocol / is supported / SSH	Yes
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes
• MSTP	No
• IEEE 1588 profile default	No
Standards, specifications, approvals	
Standard	
• for EMC	
• from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213 -M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4:2007 (Class A)
• for interference immunity	EN 61000-6-2:2005
Verification of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
• Railway application in accordance with EN 50155	No
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com

