## **SIEMENS**

## **Data sheet**

## 6GK5324-0BA00-2AR3

SCALANCE XR324WG; managed IE switch; 19" rack; 24 x 10/100 Mbps electrical ports; LED diagnostics; reset button; console port; PROFINET device; IEC 62443-4-2 certified network management function; redundancy manager; power supply 24 V DC;



product type designation	SCALANCE XR324 WG	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	24; RJ45	
number of 10/100 Mbit/s RJ45 ports / integrated	24	
interfaces / other		
number of electrical connections		
<ul> <li>for operator console</li> </ul>	1	
<ul> <li>for power supply</li> </ul>	1	
type of electrical connection		
<ul><li>for power supply</li></ul>	2 x 2-pin terminal block	
supply voltage, current consumption, power loss		
type of voltage supply / redundant power supply unit	No	
type of voltage / 1 / of the supply voltage	DC	
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V	
<ul><li>power loss [W] / 1 / rated value</li></ul>	7.2 W	
<ul><li>supply voltage / 1 / rated value</li></ul>	19.2 28.8 V	
<ul><li>consumed current / 1 / maximum</li></ul>	0.3 A	
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	2 x 2-pole terminal block	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	0 60 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP30	
design, dimensions and weights		
design	19" rack	
number of modular height units / relating to 19-inch cabinet	1	
width	483 mm	
height	44 mm	
depth	127 mm	
net weight	2.7 kg	

fastening method	
<ul> <li>19-inch installation</li> </ul>	Yes
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	No
<ul><li>wall mounting</li></ul>	No
<ul> <li>S7-300 rail mounting</li> </ul>	No
S7-1500 rail mounting	No
product features, product functions, product components	/ general
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	50
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	ng
product function	
• CLI	Yes
<ul> <li>web-based management</li> </ul>	Yes
MIB support	Yes
TRAPs via email	Yes
<ul><li>configuration with STEP 7</li></ul>	Yes
• RMON	Yes
<ul><li>port mirroring</li></ul>	Yes
<ul> <li>multiport mirroring</li> </ul>	No
• CoS	Yes
PROFINET IO diagnosis	Yes
PROFINET conformity class	В
network load class / acc. to PROFINET	2
product function / switch-managed	Yes
protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• GMRP	No
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
IGMP (snooping/querier)	Yes
identification & maintenance function	v.
I&M0 - device-specific information	Yes
I&M1 – higher level designation/location designation	Yes
product functions / diagnostics	
product function	v.
• port diagnostics	Yes
• statistics Packet Size	Yes
statistics packet type	Yes
error statistics	Yes
SysLog	Yes
product functions / VLAN	
product function	
<ul> <li>VLAN - port based</li> </ul>	Yes
<ul> <li>VLAN - protocol-based</li> </ul>	No
<ul> <li>VLAN - IP-based</li> </ul>	No
VLAN dynamic	Yes
number of VLANs / maximum	257
number of VLANs - dynamic / maximum	257
number of VLANs / at ring redundancy (HRP; MRP; standby link)	35
protocol / is supported / GVRP	No

product functions / DHCP	
product function	
DHCP client	Yes
DHCP Option 82	Yes
DHCP Option 66	Yes
DHCP Option 67	Yes
product functions / redundancy	
product function	
<ul> <li>ring redundancy</li> </ul>	Yes
<ul> <li>High Speed Redundancy Protocol (HRP)</li> </ul>	Yes
<ul> <li>high speed redundancy protocol (HRP) with redundancy manager</li> </ul>	Yes
<ul> <li>high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
<ul> <li>media redundancy protocol (MRP) with redundancy manager</li> </ul>	Yes
<ul> <li>redundancy procedure STP</li> </ul>	Yes
<ul> <li>redundancy procedure RSTP</li> </ul>	Yes
<ul> <li>redundancy procedure MSTP</li> </ul>	No
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
passive listening	Yes
protocol / is supported	
• STP/RSTP	Yes
• STP	Yes
• RSTP	Yes
• MSTP	No
RSTP big network support	Yes
LACP  Product functions / security	No
product functions / security product function	
ACL - MAC-based	Yes
ACL - port/MAC-based	Yes
• IEEE 802.1x (radius)	Yes
broadcast/multicast/unicast limiter	Yes
broadcast blocking	Yes
protocol / is supported	
• SSH	Yes
product functions / time	
product function	
SICLOCK support	Yes
protocol / is supported	
• NTP	Yes
• SNTP	Yes
IEEE 1588 profile default	No
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1, UL 61010-2-201
• for emitted interference	EN 61000-6-4 (Class B)
for interference immunity	EN 61000-6-2
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
MTBF	56 y
reference code	

KF • acc. to IEC 81346-2 according to IEC 81346-2:2019 **KFE** standards, specifications, approvals / CE Yes certificate of suitability / CE marking standards, specifications, approvals / hazardous environments standard / for hazardous zone EN 60079-0: 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 **ATEX 0145X** • from CSA and UL ANSI/ISA 12.12.01, CAN/CSA C22.2 No. 213-M1987 certificate of suitability ATEX Yes; EN 60079-0, EN60079-15, Ex II 3 G Ex nA II T4 KEMA 07 ATEX 0145X IECEx Yes; IEC 60079-0, IEC 60079-15, IECEx DEK 14.0025X, Ex nA IIC T4 Gc · CCC / for hazardous zone according to GB standard Yes standards, specifications, approvals / other certificate of suitability C-Tick Yes KC approval Yes • railway application in accordance with EN 50155 Nο further information / internet-Links Internet-Link • to web page: selection aid TIA Selection Tool http://www.siemens.com/tia-selection-tool • to website: Industrial communication http://www.siemens.com/simatic-net • to website: Industry Mall https://mall.industry.siemens.com • to website: Information and Download Center http://www.siemens.com/industry/infocenter • to website: Image database http://automation.siemens.com/bilddb • to website: CAx-Download-Manager http://www.siemens.com/cax • to website: Industry Online Support https://support.industry.siemens.com security information security information Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified: 11/6/2021 [7]