

Product-type designation

MM492-2LH



SCALANCE X-400 ACCESSORIES,
MEDIA MODULE MM492-2LH,
2 X 1GBIT/S SINGLEMODE SC,
HOT SWAPABLE, INSCRIPTION SPACE

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of optical connections / for network components or terminal equipment / maximum	2
Number of 1000 Mbit/s SC ports (LX)	2
Design of optical connections / for network components or terminal devices	SC
Connectable optical power relative to 1 mW	
• of the transmitter output	-6 ... +0 dB
• of the receiver input / maximum	-3 dB
Optical sensitivity relative to 1 mW / of the receiver input / minimum	-23 dB
Attenuation / of fiber-optic cable transmission link / minimum necessary	3 dB
Range / at the optical interface / depending on the optical fiber used	8 ... 40 km

Permitted ambient conditions

Ambient temperature	
• during operating	-40 ... +70 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C

Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Design, dimensions and weight	
Design	Media module
Width	35 mm
Height	145 mm
Depth	90 mm
Net weight	0.25 kg
Mounting type	
• Installation in media module slot	Yes
Mounting type	Latched
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1-03
• for hazardous area / of CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4:2001 (Class A)
• for interference immunity	EN 61000-6-2:2001
Verification of suitability	EN 61000-6-2:2001, EN 61000-6-4:2001
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

letzte Änderung:

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

Aug 6, 2014