

Product-type designation

SCALANCE XR528-6M



SCALANCE XR528-6M;
MANAGED IE SWITCH LAYER3 PREPARED 19",RACK
DATA CABLE OUTLET BACK SIDE,
4 X 1000/10000MBIT/S SFP PLUS;
6 X 100/1000MBIT/S 4-PORT- MEDIA MODULE,
ELECTRICAL, ELECTRICAL POE OR OPTICAL;
LED-DIAGNOSTICS;
FAULT SIGNAL CONTACT;
SELECT/SET-BUTTON;
PROFINET-IO DEVICE;
NETWORK- MANAGEMENT;
INTEGRATED REDUNDANCY-MANAGER;
OFFICE FEATURES (RSTP, VLAN, IGMP,...);
C-PLUG IN THE SCOPE OF SUPPLY

Transmission rate

Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s
Transfer rate / 3	1000 Mbit/s
Transfer rate / 4	10 Gbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	28
Number of electrical connections	
• for SFP+/SFP	4
• for operator console	1
• for management purposes	1
• for signaling contact	1
• for media module	6
• for power supply	1
• for redundant power supply	1
Design of electrical connection	
• for network components and terminal equipment	Dependent on selected media modules
• for Power-over-Ethernet / for network components or terminal equipment	RJ45 port

• for operator console • for management purposes • for signaling contact • for power supply	RJ11 port RJ45 port 2-pole terminal block 4-pole terminal block
Design of optical interface / for optical waveguide	
• at 100 Mbit/s • at 1000 Mbit/s • at 10 Gbit/s	Dependent on selected media modules Dependent on selected media modules Depending on selected SFP+ plug-in transceiver
design of the removable storage / C-PLUG/KEY-PLUG	Yes
Signal-Inputs/outputs	
Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage / external	24 V
• minimum • maximum	19.2 V 28.8 V
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	F 15 A / 125 V
Permitted ambient conditions	
Ambient temperature	
• during operating • during storage • during transport	0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Design, dimensions and weight	
Design	19" rack
Width	449 mm
Height	87.2 mm
Depth	305 mm
Net weight	10 kg
Mounting type / 19-inch installation	Yes
Type of cable outlet	Cable outlet at rear
Product properties, functions, components / general	
Cascading in cases of star structuring	Any (depending only on signal propagation time)
Product functions / management, configuration	
Product function	
• CLI	Yes

• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• RMON	Yes
• Port mirroring	Yes
• CoS	Yes
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	Yes
• GMRP	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / Diagnosis	
Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes
• SysLog	Yes
Product functions / VLAN	
Product function	
• VLAN - port based	Yes
• VLAN - protocol-based	Yes
• VLAN - IP-based	Yes
• VLAN dynamic	Yes
Number of VLANs / maximum	255

Number of VLANs - dynamic / maximum	255
Protocol / is supported / GVRP	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
• DHCP Option 82	Yes
• DHCP Option 66	Yes
• DHCP Option 67	Yes
Product functions / Routing	
Service / Routing / Note	IP routing in combination with KEY-PLUG XR-500, IPv6 available soon
Product function	
• static IP routing	Yes
• static IP routing IPv6	No
• dynamic IP routing	Yes
• dynamic IP routing IPv6	No
Protocol / is supported	
• RIPv2	Yes
• RIPv6	No
• OSPFv2	Yes
• OSPFv3 for IPv6	No
• VRRP	Yes
• VRRP for IPv6	No
Product functions / Redundancy	
Product function	
• Ring redundancy	Yes
• Redundancy manager	Yes
• Standby redundancy	Yes
• High Speed Redundancy Protocol (HRP)	Yes
• Media Redundancy Protocol (MRP)	Yes
• redundancy procedure STP	Yes
• redundancy procedure RSTP	Yes
• redundancy procedure MSTP	Yes
• Passive listening	Yes
Protocol / is supported	
• LACP	Yes
Product functions / Security	
Product function	
• ACL - MAC-based	Yes
• ACL - port/MAC-based	Yes

• IEEE 802.1X (radius)	Yes
• Broadcast/Multicast/Unicast Limiter	Yes
• broadcast blocking	Yes
Protocol / is supported / SSH	Yes
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported	
• NTP	Yes
• SNTP	Yes
Type of time synchronization	IEEE 1588 available soon
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-0: 2009, EN60079-15: 2010, II 3 G Ex nA IIC T4 Gc, KEMA 07 ATEX 0145 X
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1-03
• for hazardous area / of CSA and UL	ISA 12.12.01-2012 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Verification of suitability	EN 61000-6-2, EN 61000-6-4
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com
Security information	

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates.

For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>.

To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>.
(V3.4)

letzte Änderung:

Aug 9, 2014