

Product-type designation

SCALANCE S623



SCALANCE S 623 MODULE FOR PROTECTION OF UNITS AND NETWORKS IN AUTOMATION TECHNOLOGY AND FOR PROTECTION OF INDUSTRIAL COMMUNICATION VIA VPN AND FIREWALL;
ADDITIONAL DMZ-PORT FOR CONNECTING AN ADDITIONAL NETWORK
ADDITIONAL FUNCTIONS:
ADDRESS CONVERSION

Transmission rate

Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s
Transfer rate / 3	1000 Mbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	3
Number of electrical connections	
• for internal network	1
• for external network	1
• for DMZ	1
• for signaling contact	1
• for power supply	1
• for redundant power supply	1
Design of the electrical connection	
• for internal network	RJ45 port
• for external network	RJ45 port
• for DMZ	RJ45 port
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block

design of the removable storage / C-PLUG	Yes
Signal-Inputs/outputs	
Operating voltage / of signaling contacts / at DC / rated value	24 V
Operating current / of signaling contacts / at DC / maximum	0.1 A
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage / external	24 V
• minimum	19.2 V
• maximum	28.8 V
Consumed current / maximum	0.6 A
Product component / fusing at power supply input	Yes
Type of fusing / at input for supply voltage	Non-replaceable melting fuse (F 3 A / 32 V)
Active power loss	
• at 24V / for DC / typical	6.96 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-40 ... +60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Design, dimensions and weight	
Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.81 kg
Mounting type	
• 35 mm DIN rail mounting	Yes
• S7-300 rail mounting	Yes
• wall mounting	Yes
Mounting type	Screw mounting on horizontal and vertical surfaces
Product function / DynDNS client	Yes
Protocol / is supported / PPPoE	Yes
Product function / symbolic names for IP addresses	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	Yes
Type of configuration	SCT: Security Configuration Tool (included in scope of delivery)

Product functions / Diagnosis	
Product function	
• SysLog	Yes
• Packet Filter Log	Yes
• Audit Log	Yes
• System Log	Yes
Product functions / DHCP	
Product function / DHCP server - internal network	Yes
Product functions / Routing	
Product function / static IP routing	Yes
Product functions / Security	
Design of the firewall	stateful inspection
Product function / with VPN connection	IPSec
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
Type of hashing algorithms / with VPN connection	MD5, SHA-1
Number of possible connections	128
Number of network stations / for internal network / with VPN connection	
• maximum	128
• note	Limitation only applies in bridge mode. No limitation in routing mode
Product function	
• Password protection	Yes
• bandwidth limiting	Yes
• NAT/NAPT	Yes
Product functions / Redundancy	
Product function	
• Standby redundancy	Yes
Product functions / Time	
Product function / pass on time synchronization	Yes
Protocol / is supported / NTP	Yes
Product component / Hardware real-time clock	Yes
Product property / battery-backed hardware real-time clock	Yes
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM 3611
• for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA IIT..., KEMA 07 ATEX 0145 X
• for safety / of CSA and UL	UL 60950 / CSA C22.2 No. 60950-00, UL 508 / CSA C22.2 No. 142
• for emitted interference	EN 61000-6-4 : 2007

• for interference immunity	EN 61000-6-2 : 2005
Verification of suitability	AS/NZS 2064 (Class A), EN 61000-6-2, EN 61000-6-4, marine classification pending
• CE mark	Yes
• C-Tick	Yes
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No
Accessories	
Product expansion / optional / C-PLUG	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	https://www.siemens.com/industrymall
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com
Security information	
Security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

letzte Änderung:

Aug 7, 2014