

Product-type designation	SCALANCE WLC711 (JP)
	IWLAN CONTROLLER SCALANCE WLC711; NATIONAL APPROVALS FOR USE IN JAPAN (JP); FOR 16 ACCESS POINTS; EXPANDABLE TO 48 ACCESS POINTS; REDUNDACY; LAYER 3-ROAMING; VOIP SUPPORT; POWER DISTRIBUTION; INTERNAL CAPTIVE PORTAL PLEASE NOTE NATIONAL APPROVALS!
Product description	Supports Access Points SCALANCE W786C, W788C
Acceptability for application	Basic license for 16 Access Points preinstalled, can be estended with up to 2 Capacity Upgrade License Key WLC-700
Transmission rate	
Transmission rate / with Industrial Ethernet	10 ... 1000 Mbit/s
Interfaces	
Number of electrical connections	
for network components and terminal equipment	2
for power supply	1
Design of the electrical connection	
for network components and terminal equipment	RJ45 socket
for power supply	2-pole screw terminal
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage / 1 / from terminal block	24 V
Consumed current / at 24 V / with DC / typical	4 A
Active power loss / at 24V / for DC / typical	20 W
Permitted ambient conditions	
Ambient temperature	
during operating	5 ... 40 °C

• during storage	-40 ... +60 °C
• during transport	-40 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP20
Design, dimensions and weight	
Width	262 mm
Height	142 mm
Depth	47 mm
Net weight	2 kg
Mounting type	
• wall mounting	Yes
Mounting type	Wall mounting using the supplied mounting brackets
Product functions / management, configuration	
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• WDS	Yes
Protocol / is supported	
• Address Resolution Protocol (ARP)	No
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• DCP	No
• LLDP	No
Product functions / Diagnosis	
Product function / SysLog	Yes
Product functions / VLAN	
Product function / function VLAN with IWLAN	Yes
Product functions / DHCP	
Product function	
• DHCP client	No
Product functions / Security	
Product function	
• IEEE 802.1X (radius)	Yes

• NAT/NAPT	No
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported / SSH	Yes
Product functions / Time	
Protocol / is supported	
• NTP	Yes
• SNTP	No
• SIMATIC Time	No
Product functions / IWLAN controller	
Number of supported access points	
• in standard mode with one IWLAN controller	48
• in redundancy mode with two IWLAN controllers	96
Number of supported WLAN clients / per IWLAN controller	512
Number of VNS segments / per IWLAN controller	8
Product function	
• of the IWLAN controller	If delivered with basic license, 16 access points can operated in standard mode and 32 access points can operate in redundant mode. A capacity upgrade permits 48 access points in standard mode and 96 access points in redundant mode.
• Pre-standard (CAPWAP)	Yes
• integrated VLAN-VNS	Yes
• auto-detection of new access points	Yes
• CDR/RADIUS accounting	Yes
• Dynamic Radio Management	Yes
• VoIP QoS mapping (DSCP/TCP-on-WMM)	Yes
• VoIP roaming between IP subnets	Yes
• VoIP roaming between several IWLAN controllers	Yes
Load distribution function	DRM (Dynamic Radio/ RF Management), Packet Fairness, Flexible Client Access (Airtime Fairness), Load Balancing, Band-Steering
Backup function for IWLAN controller	Redundancy mode with two IWLAN controllers (with full capacity upgrade for both controllers, both controllers can be operated with 48 access points each. If one controller fails, the remaining controller can handle 96 access points.)
Switching function	Traffic bridged at controller/traffic bridged locally at wireless access point
Design of interface / for public network access	Internal captive portal (web redirection)
Standards, specifications, approvals	
Standard	
• for EMC / from FM	-
• for safety / of CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1, UL 508 CAN/CSA C22.2 No. 142

Verification of suitability

- CE mark
- EC declaration of conformity
- C-Tick
- Railway application in accordance with EN 50155
- E1 approval
- NEMA4X
- Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af
- Power-over-Ethernet according to IEEE802.3at for type 2

Yes
Yes
Yes
No
No
No
No
No

Standard for wireless communication

- IEEE 802.11a
- IEEE 802.11b
- IEEE 802.11e
- IEEE 802.11g
- IEEE 802.11h
- IEEE 802.11i
- IEEE 802.11n

Yes
Yes
Yes
Yes
Yes
Yes
Yes

Wireless approval

You can find the current list of countries at:
www.siemens.com/simatic-net/ik-info

Accessories

Accessories

24 V DC screw terminal and 2 mounting brackets included in the scope of delivery

Further Information / Internet Links

Internet-Link

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://www.siemens.com/industrymall>
<http://www.siemens.com/automation/net/catalog>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<http://support.automation.siemens.com>

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates.

For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>.

To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>.
(V3.4)

letzte Änderung:

Aug 7, 2014