

Product-type designation

SCALANCE W786-1PRO



IWLAN ACCESS POINT SCALANCE W786-1PRO,
ONLY FOR USE IN USA,
IEEE 802.11B/G/A/H,
INDUSTRIAL WIRELESS LAN (IWLAN) 2.4/5 GHZ,
UP TO 54MBIT/S, WPA2/802.11i/11E,
NOTE NATIONAL APPROVALS, 48VDC,
IP65(-40-+70 DGR C),
2X EXT. ANTENNA CONNECTIONS,
1 RADIO INTERFACE,
FO (GLASS-FO, MULTIMODE) SOCKET,
SCOPE OF SUPPLY: MOUNT. MAT.,
MANUAL ON CD ROM, GERMAN/ ENGLISH;
48VDC TERMINAL BLOCK

Transmission rate

Transmission rate

- with W-LAN / maximum
- with Industrial Ethernet
- note

54 Mbit/s

10 ... 100 Mbit/s

Due to the simultaneous use of several radio channels, a transmission rate of 108 Mbit/s is possible (turbo mode)

Interfaces

Number of electrical connections

- for power supply
- for redundant power supply

1

1

Design of the electrical connection

- for power supply

2-pole connector (48 V DC) or optionally available power supply adapter (4-pole 12 to 24 V DC or 3-pole 100 to 240 V AC)

Number of optical interfaces / for optical waveguide / at 100 Mbit/s

1

Design of optical interface / for optical waveguide / at 100 Mbit/s

Duplex multimode FOC (ST)

design of the removable storage / C-PLUG

Yes

Interfaces / wireless

Number of radio cards / permanently installed

1

Number of electrical connections / for external antenna(s)

2

Design of the electrical connection / for external antenna(s)

R-SMA (socket)

Product property / external antenna can be mounted directly on device	No
Supply voltage, current consumption, power loss	
Type of / supply voltage	DC
Supply voltage	
• 1 / from terminal block	48 V
• from Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	48 V
• from optional integratable power supply	
• with AC	100 ... 240 V
• with DC	12 ... 24 V
Current consumed	
• at 24 V / with DC / typical	0.34 A
• at 48 V / with DC / typical	0.17 A
• at 230 V / with AC / typical	0.04 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.34 A
Effective power loss	
• at 24V / for DC / typical	8 W
• at 48 V / with DC / typical	8 W
• at 230 V / with AC / typical	8 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	8 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	100 %
Protection class IP	IP65
Ambient condition / for (standard) operation mode	When using the power supply 100 to 240 V AC, an operating temperature of -40 °C to +60 °C is permissible
Design, dimensions and weight	
Width / of enclosure / without antenna	251 mm
Height / of enclosure / without antenna	251 mm
Depth / of enclosure / without antenna	72 mm
Net weight	2.24 kg
Mounting type	
• wall mounting	Yes
Mounting type	For mast mounting, 35 mm DIN rail mounting and S7-300 rail mounting, an additional support plate is required

Wireless frequencies	
Radio frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz
Product properties, functions, components / general	
Product function	
• Access Point Mode	Yes
• Client Mode	Yes
Number of SSIDs	8
Product function	
• Dual Client	No
• iHOP	No
• iPCF Access Point	No
• iPCF client	No
• iPCF-MC Access Point	No
• iPCF-MC client	No
Number of iPCF-capable radio modules	0
Product functions / management, configuration	
Number of manageable IP addresses / in client	8
Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• configuration with STEP 7 in the TIA Portal	Yes
• operation with IWLAN controller	No
• operation with Enterasys WLAN controller	No
• iQoS	Yes
• forced roaming with IWLAN	Yes
• WDS	Yes
Protocol / is supported	
• Address Resolution Protocol (ARP)	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• SNMP v1	Yes

• SNMP v2	Yes
• SNMP v3	Yes
• DCP	Yes
• LLDP	Yes
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / Diagnosis	
Product function	
• PROFINET IO diagnosis	Yes
• Link Check	Yes
• connection monitoring IP-Alive	Yes
• localization via Aeroscout	Yes
• SysLog	Yes
Product functions / VLAN	
Product function / function VLAN with IWLAN	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
• in Client Mode / DHCP server via LAN	Yes
Product functions / Redundancy	
Protocol / is supported / STP/RSTP	Yes
Product functions / Security	
Product function	
• ACL - MAC-based	Yes
• Management security, ACL-IP based	No
• IEEE 802.1X (radius)	Yes
• NAT/NAPT	Yes
• access protection according to IEEE802.11i	Yes
• WPA/WPA2	Yes
• TKIP/AES	Yes
Protocol / is supported / SSH	Yes
Product functions / Time	
Protocol / is supported	
• SNTP	Yes
• SIMATIC Time	No
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4

• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
• for hazardous area / of CSA and UL	UL 1604, CSA C22.2 No. 213-M1987, CL. 1, Div. 2, GP. A,B,C,D, T4 / CL. 1, Zone 2, GP IIC, T4
Verification of suitability	
• CE mark	Yes
• EC declaration of conformity	Yes
• C-Tick	Yes
• Railway application in accordance with EN 50155	No
• E1 approval	Yes
• NEMA4X	Yes
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
Standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes
• IEEE 802.11n	No
Wireless approval	For operation in the USA, you can find more detailed information at: www.siemens.com/simatic-net/ik-info
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	Yes
• Lloyds Register of Shipping (LRS)	Yes
• Nippon Kaiji Kyokai (NK)	Yes
• Polski Rejestr Statkow (PRS)	No
Accessories	
Accessories	48 V DC terminal block included in scope of delivery
Further Information / Internet Links	
Internet-Link	
• to website: Industry Mall	https://www.siemens.com/industrymall
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates.

For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>.

To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>.
(V3.4)

letzte Änderung:

Aug 7, 2014