

Product-type designation

SCALANCE W788C-2 RJ45



IWLAN ACCESS POINT,
SCALANCE W788C-2 RJ45,
FOR USE WITH IWLAN-CONTROLLER,
2 RADIOS, 6 R-SMA ANT.CONNECT.,
IEEE 802.11A/B/G/H/N, 2.4/5GHZ,
BRUTTO 450 MBIT/S PRO RADIO,
1 X RJ45 (MAX. 1 GBIT/S), POE, 2X24VDC,
IP30 (-20-+60 DGR C), POE,
WPA2/802.11I/E,
NOTE NAT. APPROVALS CONTROLLER! SCOPE OF
SUPPLY: MANUALS ON CD ROM GERMAN/ENGLISH,
2 X TERMINAL BLOCK

Transmission rate

Transfer rate

- with W-LAN / maximum 450 Mbit/s
- with Industrial Ethernet 10 ... 1000 Mbit/s

Interfaces

Number of electrical connections

- for network components and terminal equipment 1
- for power supply 1
- for redundant power supply 1

Design of the electrical connection

- for network components and terminal equipment RJ45 socket
- for power supply 4-pole screw terminal, PoE

design of the removable storage / C-PLUG

No

Interfaces / wireless

Number of radio cards / permanently installed

2

Number of electrical connections / for external antenna(s)

6

Design of the electrical connection / for external antenna(s)

N-Connect (socket)

Product property / external antenna can be mounted directly on device

Yes

Supply voltage, current consumption, power loss

Type of / supply voltage	DC
Supply voltage	
• from Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	48 V
• from Power-over-Ethernet according IEEE802.3at for type 2	50 V
Current consumed	
• at 24 V / with DC / typical	0.63 A
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	0.22 A
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	0.3 A
Active power loss	
• at 24V / for DC / typical	15 W
• with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical	10.7 W
• with Power-over-Ethernet according to IEEE802.3at for type 2 / typical	15 W
Permitted ambient conditions	
Ambient temperature	
• during operating	-20 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	90 %
Protection class IP	IP30
Design, dimensions and weight	
Width / of enclosure / without antenna	200 mm
Height / of enclosure / without antenna	158 mm
Depth / of enclosure / without antenna	79 mm
Net weight	1.7 kg
Mounting type	
• S7-300 rail mounting	Yes
• wall mounting	Yes
Wireless frequencies	
Radio frequency	
• for WLAN in 2.4 GHz frequency band	2.41 ... 2.48 GHz
• for WLAN in 5 GHz frequency band	4.9 ... 5.8 GHz
Product properties, functions, components / general	
Product function	
• Access Point Mode	Yes
• Client Mode	No

Number of SSIDs	16
Product functions / management, configuration	
Product function	
• operation with IWLAN controller	Yes
• operation with Enterasys WLAN controller	Yes
Product functions / DHCP	
Product function	
• DHCP client	Yes
Product functions / Time	
Protocol / is supported	
• SIMATIC Time	No
Standards, specifications, approvals	
Standard	
• for EMC / from FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4
• for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
• for safety / of CSA and UL	UL 60950-1 CSA C22.2 No. 60950-1
Verification of suitability	
• CE mark	Yes
• EC declaration of conformity	Yes
• C-Tick	Yes
• CCC	No
• Railway application in accordance with EN 50155	No
• fire protection in accordance with EN 45545-2	No
• E1 approval	Yes
• NEMA TS2	No
• IEC 61375	No
• IEC 61850-3	No
• NEMA4X	No
• Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af	Yes
• Power-over-Ethernet according to IEEE802.3at for type 2	Yes
Standard for wireless communication	
• IEEE 802.11a	Yes
• IEEE 802.11b	Yes
• IEEE 802.11e	Yes
• IEEE 802.11g	Yes
• IEEE 802.11h	Yes
• IEEE 802.11i	Yes

• IEEE 802.11n	Yes
Wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen
Marine classification association	
• American Bureau of Shipping Europe Ltd. (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Germanische Lloyd (GL)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (NK)	No
• Polski Rejestr Statkow (PRS)	No
Accessories	
Accessories	24 V DC screw terminal and screw terminal for digital input and output included in the scope of delivery
letzte Änderung:	Jul 28, 2014