

Product-type designation

Antenna ANT793-6DT



IWLAN ANTENNA ANT 793-6DT MIMO ANTENNA WITH WEAK DIRECTIONAL EFFICIENCY INCL. 3X QMA-SOCKETS;
8 DBI;
IP67 (-40-+85DGR C), 5GHZ;
WI-FI COMPLIANCE AND PLEASE NOTE NATIONAL APPROVALS;
WALL OR MAST MOUNTING;
COMPACT INSTRUCTIONS ON PAPER GERMAN / ENGLISH;
SCOPE OF SUPPLY: 1X ANT793-6DT,
1X MOUNTING ALIGNMENT AID

Wireless frequencies

Radio frequency

- for WLAN in 5 GHz frequency band 1
 - initial value
 - end value

5.15 GHz

5.875 GHz

Electrical data

Impedance

50 Ω

Polarization

3 ports: vertical, +/- 45° slant

Radiation characteristic

directional

Antenna gain compared to spherical radiator / of the WLAN antenna

- in the 5 GHz frequency band

8 dB

Standing wave ratio VSWR / maximum

1.7

Beam angle of antenna

- in the 5 GHz frequency band

- horizontal

65 °

- vertical

65 °

Angle of inclination / downward / maximum

0 °

Crosstalk attenuation / between the antenna connections

17 dB

Transmit power / maximum

2 W

Transmit power / Note

at 25° ambient temperature

Permitted ambient conditions

Ambient temperature

- during operating -40 ... +85 °C
- during storage -40 ... +85 °C
- during transport -40 ... +85 °C

Protection class IP

IP67

Wind load / maximum

15 N

Wind load / Note

frontal at 160 km/h

Design, dimensions and weight

Width

80 mm

Height

101 mm

Depth

35 mm

Net weight

270 g

Mounting type

- mast mounting Yes
- wall mounting Yes
- roof mounting No
- No

Material / of outer shell

Lexan EXL 9330

Standards, specifications, approvals

Verification of suitability

- RoHS conformity Yes
- UL-registration
- note UL94-V0, UL746C F1

Wireless approval

Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen

letzte Änderung:

Jul 21, 2014