## **SIEMENS**

## **Data sheet**

## 6GK5795-4MC00-0AA3

## Product type designation



IWLAN ANTENNA ANT 795-4MC WITH OMNIDIRECTIONAL CHARACTERISTIC; INCL. N-CONNECT MALE CONNECT. STRAIGHT; ANTENNA GAIN: 3/5 DBI; IP65 (-20-+60DGR C), 2.4/5GHZ; PLEASE NOTE WI-FI COMPLIANCE AND NATIONAL APPROVALS; DIRECT MOUNTING TO SCALANCE W WITH N-CONNECT CONNECT. METHOD; SCOPE OF SUPPLY:1X ANT795-4MC COMPACT INSTRUCTIONS ON PAPER GERMAN / ENGLISH



| Wireless frequencies                                   |                |
|--|----------------|
| Type of mobile network / is supported                  | WLAN           |
| Operating frequency                                    |                |
| <ul> <li>for WLAN in 2.4 GHz frequency band</li> </ul> | 2.4 2.4835 GHz |
| <ul> <li>for WLAN in 5 GHz frequency band 1</li> </ul> | 5.15 5.35 GHz  |
| • for WLAN in 5 GHz frequency band 2                   | 5.725 5.85 GHz |

| Electrical data   |                 |
|---|-----------------|
| Impedance   | 50 Ω            |
| Polarization  | linear vertical |
| Radiation characteristic  | omnidirectional |
| Antenna gain compared to spherical radiator                                 |                 |
| <ul> <li>of the WLAN antenna / in the 2.4 GHz<br/>frequency band</li> </ul> | 3 dB            |
| <ul> <li>of the WLAN antenna / in the 5 GHz frequency<br/>band</li> </ul>   | 5 dB            |
| Standing wave ratio (VSWR) / maximum  | 2               |
| Radiating angle of the antenna  |                 |
| • in the 2.4 GHz frequency band / horizontal                                | 360°            |

| • in the 5 GHz frequency band / horizontal                              | 360°  |
|---|---|
| Number of electrical connections / of the antenna                       | 1   |
| Type of electrical connection / of the antenna                          | N-Connector   |
| Design of plug-in connection  | male, straight  |
| Angle of inclination / downward / maximum                               | 0°  |
| Mechanical data   |   |
| Material  |   |
| • of outer shell  | Polycarbonate   |
| Permitted ambient conditions  |   |
| Ambient temperature   |   |
| <ul><li>during operation</li></ul>                                      | -20 +65 °C  |
| during storage  | -20 +65 °C  |
| during transport  | -20 +65 °C  |
| Protection class IP   | IP65  |
| Design, dimensions and weight   |   |
| Width   | 35 mm   |
| Height  | 160 mm  |
| Depth   | 13 mm   |
| Net weight  | 35 g  |
| Mounting type   |   |
| <ul><li>mast mounting</li></ul>   | No  |
| wall mounting   | No  |
| • roof mounting   | No  |
| • directly on the device  | Yes   |
| Product properties, functions, components / genera                      | al  |
| Product feature / silicon-free  | Yes   |
| Standards, specifications, approvals                                    |   |
| Wireless approval   | Current national approvals can be found on the Internet under |
|   | www.siemens.com/funkzulassungen                               |
| Further Information / Internet Links                                    |   |
| Internet-Link   |   |
| <ul> <li>to website: Selector SIMATIC NET<br/>SELECTION TOOL</li> </ul> | http://www.siemens.com/snst                                   |
| • to website: Industrial communication                                  | http://www.siemens.com/simatic-net                            |
| • to website: Industry Mall   | https://mall.industry.siemens.com                             |
| • to website: Information and Download Center                           | http://www.siemens.com/industry/infocenter                    |
| • to website: Image database  | http://automation.siemens.com/bilddb                          |
| to website: CAx Download Manager  | http://www.siemens.com/cax                                    |
| to website: Industry Online Support                                     | https://support.industry.siemens.com                          |
|   |   |

last modified: 10/14/2016