

IWLAN RCOAX N-CONNECT/N-CONNECT FEMALE/ FEMALE  
 PANEL FEEDTHROUGH 2.4GHZ AND 5 GHZ CABINET CABLE  
 DUCT FOR WALL THICKNESS MAX. 4.5MM



| Electrical data                                      |                                                                                     |
|------------------------------------------------------|-------------------------------------------------------------------------------------|
| Number of electrical connections                     | 2                                                                                   |
| Type of electrical connection                        | N-Connect female/N-Connect female                                                   |
| Transmission frequency                               | 0 ... 11 GHz                                                                        |
| Impedance                                            | 50 $\Omega$                                                                         |
| Permitted ambient conditions                         |                                                                                     |
| Ambient temperature                                  |                                                                                     |
| • during operation                                   | -30 ... +100 °C                                                                     |
| • during storage                                     | -30 ... +100 °C                                                                     |
| • during transport                                   | -30 ... +100 °C                                                                     |
| Protection class IP                                  | IP 68                                                                               |
| Design, dimensions and weight                        |                                                                                     |
| Diameter                                             | 20.7 mm                                                                             |
| Length                                               | 38 mm                                                                               |
| Net weight                                           | 55 g                                                                                |
| Standards, specifications, approvals                 |                                                                                     |
| Certificate of suitability                           |                                                                                     |
| • RoHS conformity                                    | Yes                                                                                 |
| Further Information / Internet Links                 |                                                                                     |
| Internet-Link                                        |                                                                                     |
| • to website: Selector SIMATIC NET<br>SELECTION TOOL | <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>               |
| • to website: Industrial communication               | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> |

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

24.04.2015