

Product type designation

KEY-PLUG XM-400 LAYER 3 ROUTING

KEY-PLUG XM400, REPLACEABLE MEDIUM FOR ACTIVATING OF LAYER 3 FEATURES FOR SCALANCE XM400 AND FOR SIMPLE DEVICE EXCHANGE IN CASE OF FAILURE AND FOR STORAGE OF CONFIGURATION DATA.



Permitted ambient conditions

Ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Width	24.3 mm
Height	17 mm
Depth	8.1 mm
Net weight	5 g
design of the removable storage	
• C-PLUG	No
• KEY-PLUG	Yes

Product properties, functions, components / general

Storage capacity	256 Mibyte
------------------	------------

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| <ul style="list-style-type: none">• to website: TIA Selection Tool• to website: Selector SIMATIC NET SELECTION TOOL• to the website: IWLAN• to website: Industrial communication• to website: Industry Mall• to website: Information and Download Center• to website: Image database• to website: CAx Download Manager• to website: Industry Online Support | <ul style="list-style-type: none">http://www.siemens.com/tia-selection-toolhttp://www.siemens.com/snsthttp://www.siemens.com/iwlanhttp://www.siemens.com/simatic-nethttps://mall.industry.siemens.comhttp://www.siemens.com/industry/infocenterhttp://automation.siemens.com/bilddbhttp://www.siemens.com/caxhttps://support.industry.siemens.com |
|---|---|

last modified:

10/13/2016