
6GK5907-4UA00-0AA0

Data sheet





ambient conditions	
ambient temperature	
during operation	-40 +85 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
width	17.5 mm
height	7 mm
depth	32 mm
net weight	3.1 g
product feature / conformal coating	No
product features, product functions, product components / general	
storage capacity	2048 Mibyte
standards, specifications, approvals	
MTBF	343 y
 range of validity 	At 25 °C
further information / internet-Links	
Internet-Link	
to website: TIA Selection Tool	http://www.siemens.com/tia-selection-tool
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/snst
to the website: IWLAN	http://www.siemens.com/iwlan
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com

last modified:

12/18/2020 🗗