

Product type designation

Power Supply SCALANCE PS9230 PoE
SCALANCE PS924 POE POWER SUPPLY FOR POWER- OVER-
ETHERNT, INPUT: 24 V DC OUTPUT: 54 V / 1.6 A DC NEC CLASS
2



Type of current supply	Input: DC 24 V, Output: DC 54 V / 1.6 A, NEC CLASS 2
Suitability for use	Power supply for PoE
Electrical data / Input	
Voltage curve / at input	DC
Supply voltage / Rated value	24 V
Supply voltage / rated value	19.2 ... 28.8 V
Type of voltage / of the supply voltage	DC
Consumed current / at rated supply voltage / maximum	4.1 A
Design of input / wide range input	No
Buffering time / at rated output current / in the event of power failure / minimum	5 ms
Current limitation / of inrush current / at 25 °C / maximum	10 A
Fuse protection type / at input	Fuse T 15A soldered
Electrical data / Output	
Voltage curve / at output	Controlled, isolated DC voltage, adjustable from 48 V to 54 V
Output voltage / at DC / Rated value	54 V

Display version / for normal operation	LED green for DC ok
Behavior of the output voltage / when switching on	Overshoot of $U_a < 2 \%$
ON-delay time / maximum	1.5 s
Voltage increase time / of the output voltage / maximum	15 ms
Output current • Rated value • Rated range	1.6 A 0 ... 1.8 A
Supplied active power / typical	86 W
Product feature / Parallel switching of channels	No
Number of parallel-switched resources / for increasing the power	0
Efficiency in percent	86 %
Power loss [W]	14 W

Electrical data / Closed-loop control

Relative overall tolerance / of the voltage	1 %
Residual ripple / maximum	0.05 V
Voltage peak / maximum	0.2 V
Relative control precision / of the output voltage • On slow fluctuation of input voltage • On slow fluctuation of ohm loading • load step of resistive load 50/100/50 % / typical • with rapid fluctuation of the input voltage by +/- 15% / typical	0.2 % 0.5 % 0.5 % 0.3 %
Setting time • load step 50 to 100% / typical • load step 100 to 50% / typical	0.5 ms 0.5 ms

Electrical data / Protection and monitoring

Design of the overvoltage protection / at output	< 60 V
Response value current limitation / typical	1.7 A
Property of the output / Short-circuit proof	Yes
Design of short-circuit protection	Electronic shutdown, automatic restart

Electrical data / Safety

Galvanic isolation / between entrance and outlet	Yes
Galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1
Operating resource protection class	Class III
Leakage current • maximum • typical	3.5 mA 0 mA

Interfaces

Number of electrical connections • for power supply	3
---	---

• for signaling contact	2
Type of electrical connection	
• for signaling contact	Screw terminal 0.5 - 2.5 mm ²
• at input	FE / + / - screw terminal 0,5 - 2,5 mm ²
• at output	2x + / 2x - , screw terminal 0.5 - 2.5 mm ²

Signal-Inputs/outputs

Product component / Signaling contact	Yes
Relay design	Normal open contact (N/O)
Operating voltage / of the signaling contacts	
• at DC / Rated value	24 V
• at DC / maximum	60 V
Operating current / of the signaling contacts	
• at DC / maximum	0.3 A
• at DC / at 30 V / maximum	0.3 A

Design, dimensions and weight

Width	42 mm
Height	125 mm
Depth	125 mm
Net weight	0.5 kg
Product feature / of the enclosure / housing for side-by-side mounting	Yes
Mounting type	
• 19-inch installation	No
• wall mounting	No
• 35 mm DIN rail mounting	Yes
• S7-300 rail mounting	No

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• Note	Convection
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Environmental category / acc. to IEC 60721	Climate class 3K3, without condensation
Protection class IP	IP20

Standards, specifications, approvals

Standard	
• for safety / from CSA and UL	cULus listed (UL508, CSA C22.2 No. 107.1)
• for emitted interference	EN 61000-6-4: 2007
• for interference immunity	EN 61000-6-2

Certificate of suitability	EN 61000-6-4: 2007
• CE marking	Yes
• C-Tick	Yes

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 29.02.2016