

Product-type designation

MM992-2 M12 GIGA

SCALANCE X ACCESSORIES 2 X 1000MBIT/S IND. ETHERNET, M12-CONN. TECHNOLOGY,ELECTRICAL MEDIA MODULE, CONFORMAL COATING



Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of 10/100/1000 Mbit/s M12 ports	2
Design of electrical connection	
for network components and terminal equipment	M12
Number of 1000 Mbit/s SC ports (SX)	2

Permitted ambient conditions

Ambient temperature	
during operating	-40 ... +70 °C
during storage	-40 ... +70 °C
during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Ambient condition / for (standard) operation mode	Conformal coating, yes
Protection class IP	IP20

Design, dimensions and weight

Design	Media module
Width	60 mm
Height	22 mm

Depth	100 mm
Net weight	0.08 kg
Mounting type	
• Installation in media module slot	Yes
Mounting type	Latched

Standards, specifications, approvals

Verification of suitability	
• CE mark	Yes
• C-Tick	Yes
• KC approval	Yes
• Railway application in accordance with EN 50155	Yes

Further Information / Internet Links

Internet-Link	
• to website: Industry Mall	http://www.siemens.com/industrial-controls/mall
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Information and Download Center	http://www.siemens.com/automation/net/catalog
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	http://support.automation.siemens.com

letzte Änderung: Aug 9, 2014