

Product type designation	<b>RUGGEDCOM SFP1132-1BX40T</b> RUGGEDCOM Accessory, Bi-directional SFP, 1000BASE-BX-D, 1 X 1000MBIT/S, LC-Interface, Optical: Single Mode Fiber Optic up to max. 40km, 1490nm TX/1310nm RX, -40...+85 Degrees Celcius compatible to RUGGEDCOM products with SFP-Slot
Suitability for operation	

### Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	1
Number of optical interfaces / for network components or terminal equipment / maximum	1
Number of 1000 Mbit/s LC ports / for multimode / Integrated	1
Design of the optical interface / for network components or terminal equipment	LC
Range / at the optical interface / depending on the optical fiber used	40 km

### Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> <li>Note</li> </ul>	-40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %

### Design, dimensions and weights

Design	SFP Module
Width	14 mm
Height	9 mm
Depth	57 mm
Net weight	0.01 kg
Product feature / conformal coating	No
Mounting type	latched

### Standards, specifications, approvals

Standard	
<ul style="list-style-type: none"> <li>for safety / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-7 EN 61000-6-4 (Class A) EN 61000-6-2

Laser protection class	Complies with 21 CFR chapter 1, subchapter J
Certificate of suitability	EN 61000-6-2, EN 61000-6-10
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• C-Tick</li> <li>• KC approval</li> <li>• E1 approval</li> <li>• IEC 61850-3</li> </ul>	<p>Yes</p> <p>No</p> <p>No</p> <p>No</p> <p>Yes</p>

**Further information / Internet-Links**

Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Industry Mall/RUGGEDCOM selector</li> <li>• to website: Siemens RUGGEDCOM</li> <li>• to website: Selector for cables and connectors</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<p><a href="http://ruggedcom-selector.automation.siemens.com">http://ruggedcom-selector.automation.siemens.com</a></p> <p><a href="http://siemens.com/ruggedcom">http://siemens.com/ruggedcom</a></p> <p><a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a></p> <p><a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a></p> <p><a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a></p> <p><a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a></p> <p><a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a></p> <p><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a></p> <p><a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a></p>

**last modified:** 12/16/2019