

Product type designation

Product description

RUGGEDCOM RMC

2 Port Ethernet Media and Speed Converter

RUGGEDCOM RMC is an industrially hardened fiber optical media converter specifically designed to operate in harsh environments such as those found in electric utility substations and factory floors. different Fiber optic types DIN rail mounting is standard

Transmission rate

Transfer rate

10 Mbit/s, 100 Mbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum

2; Options: 10BaseT to/from 10BaseFL, 100BaseTX to/from 100BaseFX

Number of electrical connections

- for network components or terminal equipment
- for power supply

1
1

Type of electrical connection

- for network components or terminal equipment
- for power supply

RJ45 port
5-pole terminal block

Number of optical interfaces

- for fiber optic cable / at 100 Mbit/s

1

Design of the optical interface

- for fiber optic cable / at 10 Mbit/s
- for fiber optic cable / at 100 Mbit/s

ST Port
MTRJ/LC Port

Range / at the optical interface / depending on the optical fiber used

2 ... 15 km

Supply voltage, current consumption, power loss

product options / wide range power supply

Yes

Supply voltage / 1 / Rated value

- Supply voltage / 1 / rated value
- Type of voltage / 1 / of the supply voltage

24 V
18 ... 36 V
DC

Supply voltage / 2 / Rated value

- Supply voltage / 2 / rated value
- Type of voltage / 2 / of the supply voltage

48 V
36 ... 59 V
DC

Supply voltage / 3 / Rated value

- Supply voltage / 3 / rated value
- Type of voltage / 3 / of the supply voltage

110 V
88 ... 300 V
DC

Supply voltage / 4 / Rated value

- Supply voltage / 4 / rated value
- Type of voltage / 4 / of the supply voltage

85 ... 265 V
AC

Product component / fusing at power supply input	Yes
Power loss [W]	
• maximum	5 W

Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• Note	A maximum ambient operating temperature of +85 °C is permissible for a duration of 16 hours
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Operating condition / fanless operation	Yes

Design, dimensions and weight

Design	Compact
Width	58 mm
Height	109 mm
Depth	94 mm
Net weight	0.68 kg
Product feature / conformal coating	optional
Material / of the enclosure	21 AWG galvanized steel enclosure
Mounting type	
• 35 mm DIN rail mounting	Yes
• 19-inch installation	No
• wall mounting	Yes

Standards, specifications, approvals

Standard	
• for EMC	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Certificate of suitability	EN 61000-6-2, EN 61000-6-10
• relating to NEMA	TS 2
• CE marking	Yes
• C-Tick	No
• IEC 61850-3	Yes
• IEEE 1613	Yes
product conformity	
• acc. to IEEE 802.3-10BaseT	Yes
• acc. to IEEE 802.3u-100BaseTX	Yes
• acc. to IEEE 802.3u-100BaseFX	Yes

Further Information / Internet Links

Internet-Link

- to website: Industry Mall/RUGGEDCOM selector <http://ruggedcom-selector.automation.siemens.com>
- to website: Siemens RUGGEDCOM <http://siemens.com/ruggedcom>
- to website: Selector for cables and connectors <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

10/07/2016